



PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS

CERTIFICATE NO.: NET6709A

Holder of certificate: Emballator Ulricehamns Bleck AB

Manufacturer: Emballator Ulricehamns Bleck AB

Box 8, (Hesters Industriområde)

SE-523 21 Ulricehamn

SWEDEN

Product:

Packaging code	Description	Drawings	Material
1A2	Steel drum, removable head	Steel pail, Drawing HE3-0227 Welded body and triple seam in bottom	Body and bottom: Steel sheet, 0.42mm

Closing mechanism:

Closure type	Material	Gasket
Clamped on lid, the lid can have a plastics	Lid: Steel sheet,	PVC compound
closure, S2 flexible pull-up spout.	0.49mm	

Photo:



Dimensions:

Packaging weight, g	Volume, litre	Height, mm	Diameter, mm
	10	225	275
	12	238	275
	15	295	275
	20	371	275
1730	25	460	275

Marking on packaging:

(f) 1A2/Y1.4/100/YR/N/NET6709A - ID

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

Telefon: +47 900 17025



INTERNATIONAL CERTIFICATE

Approval: NET issues the certification on described product according to delegated authority

from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations on Transportation of Dangerous Goods on road and railway

§ 11-1, 7th segment.

NET issues the certification on described product according to delegated authority

from Norwegian Maritime Directorate (Sjøfartsdirektoratet), RSR-13-2008

(02.09.2008).

Regulations based upon for approval: ADR, European Agreement concerning the International Carriage of Dangerous

Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

UN Recommendations on the Transport of Dangerous Goods.

IMDG, International Maritime Dangerous Goods Code, for sea transport. ICAO Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA Dangerous Goods Regulations, for the air transport.

Approval is valid for: The packaging shall always be used according to the requirements of the applicable

UN-code and its packaging instructions

Packaging groups	Content	Max. relative density	Max vapour pressure at +50°C
II and III	Liquid substances that do not adversely affect the packaging materials	1.4	114 kPa

Basis for certification: Production moved to Ulricehamns Bleck AB

Documents based upon for approval:

Report id.	Date	Issued by	Scope
93M12464A	06.12.1993	SP	Type approval
94H12223	20.10.1994	SP	Technical Evaluation
NET0323A	30.05.2008	NET	Technical Evaluation

Porsgrunn: 01.12.2008 Certificate is valid until: 31.12.2013

Geir Morten Johansen

Certification Officer

Rune Madsen Fink Control Officer

Nordisk Emballasje Testing AS Certification

Page 2 of 2 Nordisk Emballasje Testing AS Foretaksnr.: 990 793 840 Blekebakkvegen 45 N-3950 Brevik Telefon: +47 900 17025