



**PRODUCT APPROVAL OF PACKAGING  
FOR TRANSPORTATION OF DANGEROUS GOODS  
CERTIFICATE NO.: NET0357A**

HOLDER OF CERTIFICATE:  
**Greif Sweden AB**

**MANUFACTURER:** Greif Sweden AB, Box 23, SE-311 23 Falkenberg, Sweden

**MARKING ON PACKAGING:**  **1H1/Y/250/YR/N/NET0357A - ID**

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.


The packaging shall also be appropriately marked with the month of the manufacture.

**PRODUCT:**

Packaging code / Volume	Description	Drawings	Material
1H1 / 217 L	Plastics drums, non-removable head	F3P-2682 Rev. A	HDPE

**CLOSING MECHANISM:**

#: Closure type	Producer	Drawings	Material	Gasket	Torque
1: Plastic bung 70x6	Tri-Sure	TSF-2100020	Borealis BC250MO	EPDM	20 Nm
2: Plastic bung 38x6	Tri-Sure	ASP-6363	Borealis BC250MO	EPDM	20 Nm
3: Plastic bung 70x6 with 3/4"	Tri-Sure	TSF-2000032	Borealis BC250MO	PE	20 Nm



**DIMENSIONS:**

Packaging weight, g	Volume, l	Height, mm	Diameter, mm
9400 - 9870	217.0	964	590

**APPROVAL:**

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

**REGULATIONS BASED UPON FOR APPROVAL:**

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.  
 RID, International Regulations on Transport of Dangerous Goods by Rail.  
 UN Recommendations on the Transport of Dangerous Goods.  
 IMDG, International Maritime Dangerous Goods Code, for sea transport.  
 ICAO Technical Instructions for the Safe Transport of Dangerous Goods by Air.  
 IATA Dangerous Goods Regulations, for the air transport.

**APPROVAL IS VALID FOR:**

The packaging is valid for packaging group II and III containing liquid substances that do not adversely affect the packaging materials. Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	Max. relative density	Max. vapour pressure, kPa at +50°C	Closure #
n-Butylacetate	1.0	200	1,2,3
Original fluid Promyr UN3265	1.2	200	1,2
Original fluid Proens UN2920	1.2	200	1,2
Wetting solution	1.2	200	1,2,3
Water	1.2	200	1,2,3

**DOCUMENTS BASED UPON FOR APPROVAL:**

Report id.	Date	Issued by	Scope
NET0357A	01.11.2013	NET	Type approval
NET0357A-1	25.02.2014	NET	Type approval

LERUM, SWEDEN

**11.03.2014**

CERTIFICATE IS VALID UNTIL:

**31.03.2019**


Susanne E. Dalhberg  
 Certification Officer



Rune Madsen Fink  
 Control Officer

*Nordisk Emballasje Testing AS Certification*