



PRODUCT APPROVAL of PACKAGING FOR TRANSPORTATION of DANGEROUS GOODS

CERTIFICATE NO.: NET0315B

Holder of certificate: Hannells Industrier AB, Sweden

Manufacturer: Hannells Industrier AB

Box 174

SE-311 22 Falkenberg

SWEDEN

Product:

Outer packaging:

Inner packaging:

Packaging code	Description	Product identification	Material
6HA1W	Composite packaging (deviating design) The top or bottom of the steel drum is provided with a hole, diameter: 3mm.	Steel drum, Drawing: F4P-2754	Steel sheet Thickness: Mantle: 1 mm Top and bottom: 1 mm
-	Plastic receptacle	Drawing: D3P-2061	HDPE, details in reports

Closing mechanism:

Closure type	Product identification	Material in bung	Gasket	Closing torque
Two 2" plastic	Drawing D4P-2753	PP, details in report	PE	30 Nm
bungs				

Photo:





Dimensions:

Packaging weight, kg	Volume, litre	Height, mm	Diameter, mm
21.0	207	880	585

Marking on packaging:

(h) 6HA1W/Y1.6/150/YR/N/NET0315B - ID

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.



Approval:

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations on Transportation of Dangerous Goods on road and railway

§ 11-1, 7th segment.

NET issues the certification on described product according to delegated authority

from Norwegian Maritime Directorate (Sjøfartsdirektoratet) RSR-13-2008

(02.09.2008).

Regulations based upon for approval: ADR, European Agreement concerning the International Carriage of Dangerous Goods

by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

UN Recommendations on the Transport of Dangerous Goods.

IMDG, International Maritime Dangerous Goods Code, for sea transport. ICAO Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA Dangerous Goods Regulations, for the air transport.

Approval is valid for:

The packaging shall always be used according to the requirements of the applicable

UN-code and its packaging instructions.

Approval for transportation according to sub-section 6.1.1.2 in ADR and RID. Approval for transportation according to sub-section 6.1.1.2.1 in the IMDG code. Approval for transportation according to sub-section 6.3.1.18 in the ICAO TI part.

The top or bottom of the steel drum is provided with a hole diameter: 3mm

Packaging groups	Content	Max. relative density	Max. vapour pressure at +50°C
-	Liquid substances that do not adversely affect the packaging	1.6	142 kPa
	materials		

Documents based upon for approval:

Report id.	Date	Issued by	Scope
98H60773	28.12.1998	SP	Type approval
P202185	22.04.2002	SP	Additional type testing
P601002	23.03.2006	SP	Technical evaluation
142-1550-2006	31.03.2006	Swedish Rescue Agency	Approval for transportation according to sub-section 6.1.1.2 in ADR/RID
60303-06-15715	03.04.2006	The Swedish maritime administration	Approval for transportation according to sub-section 6.1.1.2.1 in the IMDG code
LS 2006-2277	04.07.2007	The Swedish civil aviation authority	Approval for transportation according to sub-section 6.3.1.18 in the ICAO TI part
NET03TE03-1	26.08.2009	NET	Technical evaluation
NET03T04	15.09.2009	NET	Additional type testing

31.03.2011 20.09.2009 Certificate is valid until: Lerum, Sweden:

Certification Officer

Rune Madsen Fink Control Officer

Nordisk Emballasje Testing AS Certification