




**PRODUCT APPROVAL OF PACKAGING
FOR TRANSPORTATION OF DANGEROUS GOODS
CERTIFICATE NO.: NET9303A**

HOLDER OF CERTIFICATE:
Haywood Roto Moulding Limited

MANUFACTURER: Haywood Roto Moulding Limited, Brook House, 221 Bowling Back Lane, Bradford BD4 8SJ, UK
Haywood Roto Moulding Limited, Green Grove Mill Dye House Lane, Rochdale OL16 2QN, UK

MARKING ON PACKAGING:  **6HH1/Y1.9/100/YR/N/NET9303A - ID**
"YR" to be replaced with the two last digits of the year.
"ID" to be replaced by any identification as decided by the manufacturer.

PRODUCT:

Packaging code	Description	Drawings	Material
6HH1, Plastics receptacle with outer plastics drum	Rotationally moulded	30L Warboy	LMDPE

CLOSING MECHANISM:

Closure type	Producer	Dimension, mm	Material	Gasket	Torque, Nm
Plain screw cap	Francis Ward	65	LMDPE	PE Foam	25
Vented screw cap	Francis Ward	65	LMDPE	PE Foam	25



DIMENSIONS:

Packaging weight (inner + outer), kg	Tare mass, kg	Volume, l	Height, mm	Diameter, mm	Neck size, mm
1.8 + 2.25	4.6	30	605	330	50

APPROVAL:

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.
 ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.
 RID, International Regulations on Transport of Dangerous Goods by Rail.
 IMDG, International Maritime Dangerous Goods Code, for sea transport.
 ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.
 IATA, Dangerous Goods Regulations, for the air transport.

APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances that do not adversely affect the packaging materials. Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	Max. relative density	Max. vapour pressure, kPa at +50°C
Water	1.9	114

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
11D19-0622	01.02.2012	Pira International	Type approval
NET9300	30.04.2015	NET	Type approval

LERUM, SWEDEN

11.05.2016 CERTIFICATE IS VALID UNTIL:

31.05.2021


 Susanne E. Dahlberg
 Certification Officer



 Rune Madsen Fink
 Control Officer

Nordisk Emballasje Testing AS Certification