




**PRODUCT APPROVAL OF PACKAGING
FOR TRANSPORTATION OF DANGEROUS GOODS
CERTIFICATE NO.: NET6712A**

HOLDER OF CERTIFICATE:
Emballator Ulricehamns Bleck AB

MANUFACTURER: Emballator Ulricehamns Bleck AB, Maskinvägen 10, SE-52321 Ulricehamn, Sweden

MARKING ON PACKAGING:  **1A2/Y2.0 Z3.0/100/YR/N/NET6712A - ID**
"YR" to be replaced with the two last digits of the year.
"ID" to be replaced by any identification as decided by the manufacturer.

PRODUCT:

Packaging code	Description	Material
1A2, steel drums, removable head	UN-pail 180 without bead.	Steel sheet TS 275 (T57)

CLOSING MECHANISM:

#: Closure type	Drawings	Material	Gasket
1: Press lid	64214-01, 160512	Steel sheet TS275 (T57)	Polyuretan
2: Ring-latch	64214-01, 160512	Plastic, polypropylen	-



DIMENSIONS:

#: Volume, l	Height, mm	Diameter, mm	Head / Body / Bottom, mm	Drawing
1: 5.0	243	180	0.25 / 0.25 / 0.30	6437-04, 131210
2: 4.0	201	180	0.25 / 0.25 / 0.30	6435-05, 140623
3: 3.0	161	180	0.25 / 0.25 / 0.30	6438-02, 140324
4: 2.5	148	180	0.25 / 0.25 / 0.30	6433-06, 130829

APPROVAL:

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.
 ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.
 RID, International Regulations on Transport of Dangerous Goods by Rail.
 IMDG, International Maritime Dangerous Goods Code, for sea transport.
 ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.
 IATA, Dangerous Goods Regulations, for the air transport.

APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances that do not adversely affect the packaging materials in accordance with table below. The packaging shall always be used according to the requirements of the applicable UN-code and its packaging instructions.

Content	Max. relative density	Max. vapour pressure at +50°C	Packaging group
Liquid	2.0	114 kPa	II
Liquid	3.0	114 kPa	III

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET6712A	21.04.2010	NET	Type approval
NET6712A-1	19.10.2011	NET	Selective testing, increased density

LERUM, SWEDEN

13.05.2016 CERTIFICATE IS VALID UNTIL:

31.05.2021


Susanne E. Dahlberg
 Certification Officer



Rune Madsen Fink
 Control Officer

Nordisk Emballasje Testing AS Certification