



PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET3274A

HOLDER OF CERTIFICATE:

DS Smith Packaging Sweden AB

MANUFACTURER: DS Smith Packaging Sweden AB, Bangårdsgatan 2-4, SE-331 26

Värnamo, SWEDEN

MARKING ON PACKAGING: 4G/X2.5/S/YR/N/NET3274A - ID

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

PRODUCT:

Packaging code	Description	Material
4G, Fibreboard boxes	Design W 0427	Details in report

CLOSING MECHANISM:

Closure type	Drawings	Material
Fibreboard lockable lid	KD07550	Details in report

INNER PACKAGING:

Туре	Drawing	Material
Inner liner	75767483	LDPE
Patent lock	Art. 95631010	HDPE
Bottle, 0.5 l	00304, Rev J, 500 ml	Glass
Screw cap	00304, Rev J	Aluminum
Gasket	V9001	Rubber
Absorbent mat	-	PP

DIMENSIONS:

Drawing	Volume, I	Length, mm	Width, mm	Height, mm
KD07550	6.7	267	205	120

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E



APPROVAL:

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

APPROVAL IS VALID FOR:

The packaging is valid for packaging group I, II and III containing liquid substances that do not adversely affect the packaging materials. The glass bottle, 0.5 litres, listed as content and part of inner packaging in this certificate, has gone through an internal hydraulic pressure test according to ADR 6.1.5.5 with test pressure 250 kPa.

Content	Max. vapour pressure, kPa at +50°C	Max. gross weight, kg
Glass bottle containing liquid	200	2.5

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET3272A	01.07.2015	NET	Type approval

LERUM, SWEDEN

02.09.2015 CERTIFICATE IS VALID UNTIL:

14.07.2016

Susanne E. Dahlberg Certification Officer

Rune Madsen Fink Control Officer

Nordisk Emballasje Testing AS Certification

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E