




**PRODUCT APPROVAL OF PACKAGING  
FOR TRANSPORTATION OF DANGEROUS GOODS  
CERTIFICATE NO.: NET0250C**

HOLDER OF CERTIFICATE:  
**RPC Packaging AS**

**MANUFACTURER:** RPC Packaging AS, avd. Kambo, Brevikveien 535, N-1506 Moss, Norway.

**MARKING ON PACKAGING:**  **3H1/Y1.4/100/YR/N/NET0250C - ID**  
 "YR" to be replaced with the two last digits of the year.  
 "ID" to be replaced by any identification as decided by the manufacturer.  
 The packaging shall also be appropriately marked with the month of the manufacture.

**PRODUCT:**

Packaging code	Description	Drawings	Material
3H1, Plastics jerricans	Non-removable head	W3405 Rev.B	Total HDPE 51090

**CLOSING MECHANISM:**

Closure type	Producer	Drawings	Material	Gasket	Torque
Screw cap, 61	RPC Promens Industrial UK	RPC Promens DIN 61 Ver.2	HDPE	EPE liner	20 Nm
Screw cap, 25	Modulpac AB	7250001	HDPE	ALKOzell	3 Nm



**DIMENSIONS:**

Volume, l	Packaging weight, g	Height, mm	Width, mm	Length, mm	Neck size, mm
25.0	1300 - 1350	440	260	295	61 / 25
20.0	1139 - 1182	370	260	295	61 / 25

**APPROVAL:**

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

**REGULATIONS BASED UPON FOR APPROVAL:**

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

**APPROVAL IS VALID FOR:**

The packaging is valid for packaging group II and III. The packaging shall always be used according to the requirements of the applicable UN-code; UN2031 and its packaging instructions; P001 and PP81. For UN2031 with more than 55% nitric acid, the permitted use of plastics jerricans as single packagings shall be two years from the date of manufacture.

Compatibility testing has been carried out according to ADR/RID Liquids listed in the table below.

Content	Max. relative density	Max. vapour pressure, kPa at +50°C
Nitric Acid 62%, UN2031	1.4	114

**DOCUMENTS BASED UPON FOR APPROVAL:**

Report id.	Date	Issued by	Scope
080025	28.03.2008	TÜV	Type approval
080124	24.10.2008	TÜV	Type approval
NET02TE07	31.10.2017	NET	Technical evaluation
NET02TE08	17.01.2018	NET	Technical evaluation, 20 l

**TEST STANDARD:**

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.



PORSGUNN, NORWAY

17.01.2018 CERTIFICATE IS VALID UNTIL:

15.03.2018

A handwritten signature in blue ink, reading 'Geir M. Johansen'.

Geir Morten Johansen  
Certification Officer

A handwritten signature in blue ink, reading 'Rune Madsen Fink'.

Rune Madsen Fink  
Control Officer

*Nordisk Emballasje Testing AS Certification*

A large, faint watermark logo in the center of the page, consisting of a stylized shield or emblem with a vertical bar through the middle.