VAT No.: 990 793 840

Bank account: 6250.05.22351

GPS: 59°03'25" N 9°40'70" E





PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NETO 1 28A

HOLDER OF CERTIFICATE:

Emballator Mellerud Plast AB

MANUFACTURER: Emballator Mellerud Plast AB, Box 83, SE-464 22 Mellerud,

SWEDEN

MARKING ON PACKAGING: (3) 3H1/Y1.2/100/YR/N/NET0128A - ID

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

The packaging shall also be appropriately marked with the month of the manufacture.

PRODUCT:

Packaging code	Description	Drawings	Material
3H1	Plastics jerricans,	D0500-410-961	B 5210
	non-removable head	20130414	
3H1	Plastics jerricans,	D0400-410-961	B 5210
	non-removable head	20120412	



DIMENSIONS:

Packaging	Volume, I	Height, mm	Width, mm	Length, mm	Neck size, mm
weight, g					
159 - 240	5.0	297	123	193	40
139 - 200	4.0	255	123	193	40

E-mail: info@net17025.com

Web: www.net17025.com



CLOSING MECHANISM:

010011101110111					
Screw cap	Producer	Drawings	Material	Gasket	Torque
1: 40 mm	Emballator	12475	Basell ACP	Cone	4 Nm
	Växjö Plast AB		6541A		
2: 40 mm	Modulpac AB	40B/ 8400001	HDPE, details in	Cone	8 Nm
			report		
3: 40 mm child	Modulpac AB	40BPP/	HDPE, details in	PET/EPE/PET	8 Nm
resistant		8400002	report		



APPROVAL:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances that do not adversely affect the packaging materials. Permeability test has been carried out according to ADR 6.1.5.7. Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	Max. relative density	Max. vapour pressure, kPa at +50°C
Water	1.2	114
Mixture of hydrocarbons	1.0	114
Acetic acid	1.1	114

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E





DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET0128A-1	23.05.2013	NET	Type approval
NET0128A	30.05.2012	NET	Type approval
P803614A	18.11.2008	SP	Type approval
NET2814A	08.01.2021	NET	Additional test, 40B

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.



BREVIK, NORWAY

04.03.2021 CERTIFICATE IS VALID UNTIL:

Rune Madsen Fink

Control Officer

31.05.2023

Geir Morten Johansen Certification Officer

Gai M. Cha

Nordisk Emballasje Testing AS Certification

NET0128A Page 3 of 3

Telephone +47 900 17025

E-mail: <u>info@net17025.com</u>

Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E