



# PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET10802A

HOLDER OF CERTIFICATE: **Greif Sweden AB** 

2000 kg max

**MANUFACTURER:** 

Greif Sweden AB, Box 23, SE-311 23 Falkenberg, Sweden



**MARKING ON PACKAGING:** 



31HA1/Y/MMYY N/NET10802A - ID 3600/1997



"MMYY" to be replaced with the month and year (last two digits) of manufacture. "ID" to be replaced by the name or symbol of the manufacturer. Each IBC shall also be marked according to 6.5.2.2.1 ADR/RID/IMDG, and each inner receptacle shall be marked according to 6.5.2.2.4 ADR/RID/IMDG.

#### **PRODUCT:**

Packaging code	Description
31HA1, Composite IBC	Rigid plastics inner receptacle; Greif Sweden
	NET0359 and outer casing of steel and pallet;
	Mauser BAM 11027



### **DIMENSIONS:**

Packaging	Tara weight, kg	Volume, I	Height, mm	Width, mm	Length, mm
IBC, plastic	53.6	1056	1160	995	1210
pallet					
IBC, hybrid skid	53.7	1056	1180	995	1210
pallet					

Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E





## **CLOSING MECHANISM:**

Closure type	Description	Drawing	Material	Torque, Nm
Screw cap #1	150 mm	2064co1rev0	HDPE	35
Screw cap #2	150 mm vented	2001co0rev3	HDPE	35
Screw cap #3	150 mm vented	TSF-21000100	HDPE	35
Screw cap #4	150 mm vented	2064co0rev2	HDPE	35
Screw cap #5	220 mm	2000co0rev4	HDPE	35
Screw cap #6	220 mm	2068co1rev0	HDPE	90
Screw cap #7	220 mm, vented	2068co0rev0	HDPE	90
Valve #1	2" integrated nut,	2017ass0rev5	HDPE/PP/fibreglass	-
	butterfly			
Valve #2	2" weldable,	2019cp1rev0	HDPE/PP/fibreglass	-
	butterfly			
Valve #3	2" plunger	2008ass0rev1	HDPE	-
Valve #4	3" integrated nut	2015ass0rev4	HDPE/PP/fibreglass	-
Valve #5, with liner	2" weldable,	2019ass0rev5	HDPE	-
	Butterfly			
Valve #6	2" integrated nut,	2055ass0rev0	HDPE/PP/fibreglass	-
	ball			
Screw cap #8	150 mm	2071ass0rev0	HDPE	35













 NET10802A
 Page 2 of 4

 Telephone
 +47 900 17025

 E-mail:
 info@net17025.com

 Web:
 www.net17025.com

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E








# **INNER PACKAGING/ACCESSORIES:**

Туре	Description	Drawing	Material
Inner receptacle Ø150	Blow moulded	2003bo0rev11	HDPE
Inner receptacle Ø220	Blow moulded	2003bo0rev11	HDPE
Outer casing	Galvanized pipe section.	O-C-11027	Steel
	Lattice-type basket		
	screwed onto a pallet		
Corner protection	Black sheets of plastic	C-P-11027	HDPE
Plastic pallet, BAM 11027	Blow moulded/Welded	P-P 11027	HDPE
Hybrid skid pallet, BAM	Galvanized steel sheet	H-S-P 11027	Plastic/Steel
11027			





#### **APPROVAL:**

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

#### **REGULATIONS BASED UPON FOR APPROVAL:**

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

NET10802A Page 3 of 4

Telephone +47 900 17025 VAT No.: 990 793 840
E-mail: info@net17025.com Bank account: 6250.05.22351
Web: www.net17025.com GPS: 59°03'25" N 9°40'70" E



#### **APPROVAL IS VALID FOR:**

The packaging shall always be used according to the requirements of the applicable UN-code and its packaging instructions. The 2" weldable butterfly valve (listed as #5) is only approved with a welded aluminum liner between neck and cap. The following test are performed and approved: Bottom lift- , drop-, leakness-, internal pressure-, stacking- and vibration test. Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	Max. relative density	Max. vapour pressure, kPa at +50°C	Packaging group
Water	1.9	114	II and III
Wetting Solution	1.6	114	II and III
Acetic Acid	1.6	114	II and III
n-Butyl acetate	1.5	114	II and III
Mixture of hydrocarbons	1.5	114	II and III
Nitric Acid	1.5	114	II and III

#### **DOCUMENTS BASED UPON FOR APPROVAL:**

Report id.	Date	Issued by	Scope	
NET0394CX	21.10.2019	NET	Type Approval, cross	
			bottling	
NET03TE39	30.10.2019	NET	Technical evaluation, P-r	
NET0359A6	10.12.2020	NET	Additional cap, #8	

#### **TEST STANDARD:**

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.

The packagings shall be manufactured, reconditioned and tested under a quality assurance programme which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.



PORSGRUNN, NORWAY

aci Ma loho

**03.05.2021** CERTIFICATE IS VALID UNTIL:

31.05.2026

Geir Morten Johansen Certification Officer Rune Madsen Fink Control Officer

Nordisk Emballasje Testing AS Certification

Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E