



PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NETO359A

HOLDER OF CERTIFICATE: **Greif Sweden AB**

2260 kg max

MANUFACTURER:

Greif Sweden AB, Box 23, SE-311 23 Falkenberg, Sweden



MARKING ON PACKAGING:

U N/NET0359A - ID 4069/2017

"MMYY" to be replaced with the month and year (last two digits) of manufacture. "ID" to be replaced by the name or symbol of the manufacturer. Each IBC shall also be marked according to 6.5.2.2.1 ADR/RID/IMDG, and each inner receptacle shall be marked according to 6.5.2.2.4 ADR/RID/IMDG.

PRODUCT:

Packaging code	Description	Material
31HA1, Composite IBC	Rigid plastics inner receptacle and	Plastic / Steel / Wood, details in
	outer casing of steel	report



DIMENSIONS:

Packaging	Tara weight, kg	Volume, I	Height, mm	Width, mm	Length, mm
IBC, wood pallet	57.2	1056	1170	1000	1200
IBC, plastic	53.2	1056	1170	1000	1200
pallet					
IBC, hybrid	53.1	1056	1160	1000	1200
pallet					

Telephone +47 900 17025

E-mail: <u>info@net17025.com</u>

Web: <u>www.net17025.com</u>





CLOSING MECHANISM:

Closure type	Description	Drawing	Material	Torque, Nm
Screw cap #1	150 mm	2064co1rev0	HDPE	35
Screw cap #2	150 mm vented	2001co0rev3	HDPE	35
Screw cap #3	150 mm vented	TSF-21000100	HDPE	35
Screw cap #4	150 mm vented	2064co0rev2	HDPE	35
Screw cap #5	220 mm	2000co0rev4	HDPE	35
Screw cap #6	220 mm	2068co1rev0	HDPE	90
Screw cap #7	220 mm vented	2068co0rev0	HDPE	90
Screw cap #8	150 mm	2071ass0rev0	HDPE	35
Valve #1	2" integrated nut,	2017ass0rev5	HDPE/PP/fibreglass	-
	butterfly			
Valve #2	2" weldable,	2019cp1rev0	HDPE/PP/fibreglass	-
	butterfly			
Valve #3	2" plunger	2008ass0rev1	HDPE	-
Valve #4	3" Integrated nut	2015ass0rev4	HDPE/PP/fibreglass	-
Valve #5, with liner	2" weldable,	2019ass0rev5	HDPE	-
	butterfly			
Valve #6	2" integrated nut,	2055ass0rev0	HDPE/PP/fibreglass	-
	ball			













 NET0359A
 Page 2 of 5

 Telephone
 +47 900 17025

 E-mail:
 info@net17025.com

 Web:
 www.net17025.com









INNER PACKAGING/ACCESSORIES:

Туре	Description	Drawing	Material
Inner receptacle Ø150	Blow moulded	2003bo0rev11	HDPE
Inner receptacle Ø220	Blow moulded	2003bo0rev11	HDPE
Outer casing	Galvanized pipe section.	2014ga0rev2	Steel
	Lattice-type basket		
	screwed onto a pallet		
Corner protection	Black sheets of plastic	FS-0003 revA	HDPE
Wood pallet	Board, plank	IBC Trä pall	Wood
Plastic pallet	Blow moulded/Welded	2066ppj0rev0	HDPE
Hybrid pallet	Standard Nuovo	2058ass0rev0	Plastic/Steel









APPROVAL:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

NET0359A Page 3 of 5

Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>





APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances that are listed in the table below.

The liquids marked with letter A - F are referring to standard liquids listed in ADR 6.1.6.1 and verified by chemical compatibility testing to this specific liquid.

The dangerous substances allowed to transport in the packaging after chemical compatibility with these liquids, are listed in the "Assimilation list" table 4.1.1.21.6 in ADR.

The packaging shall always be used according to the requirements of the applicable UN-code and its packaging instructions. The 2" weldable butterfly valve (listed as #5) is only approved with a welded aluminum liner between neck and cap.

The following test are performed and approved according to ADR:

6.5.6.4 Bottom lift test

6.5.6.6 Stacking test

6.5.6.7 Leakproofness test

6.5.6.8 Internal pressure test

6.5.6.9 Drop test

6.5.6.13 Vibration test

Max. relative	Max. vapour	Packaging group	Closure
density	pressure, kPa at		
	+50°C		
1.6	114	II and III	1-7
1.6	114	II and III	1-7
1.5	114	II and III	1-7
1.5	114	II and III	1-7
1.5	114	II and III	1-7
1.9	114	II and III	1-8
1.4	114	II and III	1-7
1.0	114	III	1-7
_			
	density 1.6 1.6 1.5 1.5 1.5 1.4	density pressure, kPa at +50°C 1.6	density pressure, kPa at +50°C 1.6

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>



DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET0359A	03.06.2016	NET	Type approval, water &
			Na
NET0359A2	29.04.2016	NET	Type testing, Wa, Aa &
			n-Ba
NET0359A3	15.08.2016	NET	Type testing, Ws
NET0359B	03.06.2016	NET	Type Approval
160058, Rev.0.	24.06.2016	TÜV	Vibration testing, plastic
			pallet
Report 100068.3	31.03.2010	TÜV	Vibration testing,
			wooden pallet
Report 100068.4	31.03.2010	TÜV	Vibration testing, hybrid
			pallet
GV/gv/T-15.039	23.10.2015	IBE-BVI	Additional cap, #4
NET0359A5	11.01.2017	NET	Additional test, increase
			of density
NET03TE33	19.05.2017	NET	Technical evaluation, cap
			#1
NET03T28	23.03.2018	NET	Additional type test, cap
			#6, #7
NET4803A	17.04.2018	NET	Additional type test,
			Kimulux Matris
NET1201T01	04.03.2019	NET	Additional test, UN3265
NET0359A6	10.12.2020	NET	Additional cap, #8

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.

The packagings shall be manufactured, reconditioned and tested under a quality assurance programme which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.



BREVIK, NORWAY **03.05.2021** CERTIFICATE IS VALID UNTIL:

31.05.2026

Geir Morten Johansen Certification Officer Rune Madsen Fink Control Officer

Nordisk Emballasje Testing AS Certification

laci Ma loho

Telephone +47 900 17025
E-mail: info@net17025.com
Web: www.net17025.com