



PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NETO366C

HOLDER OF CERTIFICATE: **Greif Sweden AB**

MANUFACTURER: Greif Sweden AB, Box 203, SE-311 23 Falkenberg, Sweden

MARKING ON PACKAGING:

() 3H1/Y1.9/200/YR/N/NET0366C - ID

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

The packaging shall also be appropriately marked with the month of the manufacture.

PRODUCT:

Packaging code	Description	Drawings	Material
3H1 / 20 L	Plastics jerricans,	FB-0021 Rev B, FB-0001	HDPE
	non-removable head	Rev B,	
3H1 / 25 L	Plastics jerricans,	FB-0022 Rev B, FB-0002	HDPE
	non-removable head	Rev B	
3H1 / 27.5 L	Plastics jerricans,	FB-0023 Rev B, FB-0003	HDPE
	non-removable head	Rev B	



DIMENSIONS:

# Jerrican	Volume, I	Height, mm	Width, mm	Length, mm	Neck size, mm
weight, g					
1: 930 - 1388	20.0	376	260	295	60
2: 980 - 1388	20.0	376	260	295	60
3: 1071 - 1598	25.0	441	260	295	60
4: 1127 - 1598	25.0	441	260	295	60
5: 1124 - 1676	27.5	470	260	295	60

Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>





CLOSING MECHANISM:

	Duaduan	Duning	Matarial	Caalcab	Taugus
#: Screw cap	Producer	Drawings	Material	Gasket	Torque
1: 60 mm	Tri-Sure	TSF-504224-2	HDPE	Washer,	25 Nm
				expanded PE	
2: 60 mm	Tri-Sure	F4P-2015	HDPE	Wad, expanded	25 Nm
				PE	
3: 60 mm	Tri-Sure	F4P-2015	HDPE	Washer,	25 Nm
				expanded PE	
4: Vented 60	Tri-Sure	TSF-504351-2	HDPE	Washer,	25 Nm
mm				expanded PE	
5: 60 mm	Bergi Plast	00-1836	HDPE	Washer, EPE	25 Nm
				300	
7: 60 mm	Kunststoff-	KTH55-SK61-16	HDPE	Washer,	25 Nm
	technik			expanded PE	
8: 60 mm	United caps	09S41LB13-01P	HDPE	Wad, Induction	25 Nm
				liner	
9: 25 mm	Modulpac AB	25PMO Rev. 3	HDPE	Wad, PET/	3 Nm
				Alkozell/PET	
10: 60 mm	United caps	BV0600C B	HDPE	Wad, ALU30my/	25 Nm
				PET12my/PE60	
				my	
11: Vented 60	Tri-Sure	TSF-505512-1	HDPE	Washer,	25 Nm
mm				expanded PE	
12: 60 mm	Tri-sure	TSF-506492	HDPE	Washer, PEfoam	25 Nm
Carbon black					
free					

APPROVAL:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>



REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances that do not adversely affect the packaging materials.

Permeability test has been carried out according to ADR 6.1.5.7. Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	Max. relative	Max. vapour	Jerrican #	Closure #
	density	pressure, kPa at		
		+50°C		
White spirit	1.0	200	All items	All items
n-Butylacetate	1.0	200	All items	All items
Acetic acid	1.2	200	All items	All items
Wetting solution	1.2	200	All items	All items
Water	1.9	200	All items	All items
Nitric acid 55 %	1.4	200	2 and 4	1 - 7, 9 and 11
Nitric acid 55-62 %	1.4	200	2 and 4	5, 7 and 9

DOCUMENTS BASED UPON FOR APPROVAL:

Date	Issued by	Scope
22.06.2016	NET	Type approval
08.08.2016	NET	Additional test, MoH
22.06.2016	NET	Type approval
08.08.2016	NET	Additional test, MoH,
		n-Ba
02.09.2016	NET	Calculation of production
		weights
02.09.2016	NET	Technical evaluation,
		pallet
11.10.2016	NET	Additional test, MoH, Ws
24.11.2016	NET	Additional test, cap 3 & 9
31.01.2017	NET	Additional test, MoH,
		anti-glug
21.10.2019	NET	Additional test, Na 62%
01.06.2021	NET	Technical evaluation
	22.06.2016 08.08.2016 22.06.2016 08.08.2016 02.09.2016 02.09.2016 11.10.2016 24.11.2016 31.01.2017	22.06.2016 NET 08.08.2016 NET 22.06.2016 NET 08.08.2016 NET 02.09.2016 NET 11.10.2016 NET 24.11.2016 NET 31.01.2017 NET

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>





TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.

The packagings shall be manufactured, reconditioned and tested under a quality assurance programme which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.



BREVIK, NORWAY

01.06.2021 CERTIFICATE IS VALID UNTIL:

Control Officer

31.10.2024

Geir Morten Johansen Certification Officer

Geir M. Cha

Nordisk Emballasje Testing AS Certification

NET0366C Page 4 of 4

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>