



PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET8001A

HOLDER OF CERTIFICATE: **Greif Scandinavia**

MANUFACTURER: Greif Scandinavia

MARKING ON PACKAGING:

(h) 3H1/X1.9/250/YR/N/NET8001A - ID

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

The packaging shall also be appropriately marked with the month of the manufacture.

PRODUCT:

Packaging code	Description	Drawings	Material
3H1 / 20 L	Plastics jerricans,	FB-0021 Rev 01,	HDPE
	non-removable head	FB-0001 Rev 03	
3H1 / 25 L	Plastics jerricans,	FB-0022 Rev 01,	HDPE
	non-removable head	FB-0002 Rev 03	
3H1 / 27.5 L	Plastics jerricans,	FB-0023 Rev 01,	HDPE
	non-removable head	FB-0003 Rev 03	
3H1 / 30 L	Plastics jerricans,	FB-0024 Rev 01,	HDPE
	non-removable head	FB-0004 Rev 03	



DIMENSIONS:

# Packaging	Volume, I	Height, mm	Width, mm	Length, mm	Neck size, mm
weight, g					
1: 1034 - 1300	20.0	376	260	295	60
2: 1200 - 1300	20.0	376	260	295	60
3: 1137 - 1500	25.0	441	260	295	60
4: 1180 - 1500	25.0	441	260	295	60

Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>





5: 1300 - 1500	25.0	441	260	295	60
6: 1500 - 1575	25.0	441	260	295	60
7: 1226 - 1524	27.5	470	260	295	60
8: 1310 - 1620	30.0	508	260	295	60
9: 1380 - 1620	30.0	508	260	295	60
10: 1500 - 1620	30.0	508	260	295	60
11: 1080-1134	20.0	376	260	295	60
12: 1180-1239	25.0	441	260	295	60
13: 1380-1449	30.0	508	260	295	60

CLOSING MECHANISM:

#: Screw cap	Producer	Drawings		Mater	ial	Gasket	Torque
1: 60 mm	Tri-Sure	TSF-504224-2		HDPE		Washer,	25 Nm
						Expended PE	
2: 60 mm	Tri-Sure	F4P-2015		HDPE		Wad, Expended	25 Nm
						PE	
3: 60 mm	Tri-Sure	F4P-2015		HDPE		Washer,	25 Nm
						Expended PE	
4: Vented 60	Tri-Sure	TSF-504351	-2	HDPE		Washer,	25 Nm
mm						Expended PE	
7: 60 mm	Bergi Plast	00-1836		HDPE		Washer, EPE	25 Nm
						300	
11: 60 mm	Kunststoff-	KTH55-SK6	1-16	HDPE		Washer,	25 Nm
	technik					expended PE	
12: 60 mm	United caps	09S41LB13-	-01P	HDPE		Induction liner	25 Nm
13: 25 mm	Modulpac AB	25PMPP/		HDPE		PET/Alkozell/PE	3 Nm
		7250001				T	





 NET8001A
 Page 2 of 4

 Telephone
 +47 900 17025

 E-mail:
 info@net17025.com

 Web:
 www.net17025.com



APPROVAL:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA Dangerous Goods Regulations, for the air transport.

APPROVAL IS VALID FOR:

The packaging is valid for packaging group I, II and III containing liquid substances that do not adversely affect the packaging materials. Permeability test has been carried out according to ADR 6.1.5.7. Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	Max. relative density	Max. vapour pressure, kPa at +50°C	Packaging #	Closure #
Acetic acid	1.2	200	All items	All items, not 12
n-Butyl acetate	1.0	200	All items	All items, not 12, 13
Nitric acid 55%	1.4	200	All items	All items, not 12, 13
Wetting solution	1.2	200	All items	All items, not 12
Water	1.9	200	All items	All items
White spirit	1.0	200	All items	All items, not 12, 13
Nitric Acid 65%	1.4	200	2, 6	7, 11
Organic Peroxide	1.2	200	2, 5	7, 11
Methyl Ethyl Ketone	1.2	200	5	11
Peroxide				
Propionic Acid	1.0	200	6	11
Promyr XR680	1.4	200	6	11
Nitric acid 62%	1.4	200	11, 12, 13	7, 11

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET8001A	01.11.2013	NET	Type approval
NET8001A2	08.04.2016	NET	Additional test, cap #13
NET03TE27	29.06.2016	NET	Technical evaluation

Telephone +47 900 17025

E-mail: <u>info@net17025.com</u>

Web: <u>www.net17025.com</u>





TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.



BREVIK, NORWAY

23.06.2021 CERTIFICATE IS VALID UNTIL:

Control Officer

30.06.2026

Geir Morten Johansen Certification Officer

Caci M. Johan

Nordisk Emballasje Testing AS Certification

NET8001A Page 4 of 4

Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>