

# **PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET0112A**

HOLDER OF CERTIFICATE:  
**Emballator Mellerud Plast AB**

**MANUFACTURER:** Emballator Mellerud Plast AB, Box 83, SE-464 22 Mellerud, SWEDEN

**MARKING ON PACKAGING:**

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 12 mm high. of an appropriate size.

The packaging shall also be appropriately marked with the month of the manufacture.



**3H1/Y1.4/150/YR  
N/NET0112A - ID**



3H1	: The United Nations symbol
Y1.4	: Plastics jerricans, non-removable head
150	: Packaging group II and III, and relativ density of the substance
YR	: Hydraulic test pressure in kPa
N	: To be replaced with the last two digits of the year of manufacture
NET0112A - ID	: Norway, the state authorizing the allocation of the mark
	: Identification of the jerrican followed by "ID" to be replaced by the name or symbol of the manufacturer

**PRODUCT:**

Description	Material
Blow moulded plastic jerrycan performed in a serie of 25, 20 and 15 litre, approved for all six of the standard liquids	HDPE, details in report



### DIMENSIONS:

Weight of the jerrican, g	Volume, l	L*W*H, mm	Neck size, mm	Drawing
1125-1400	25.0	285*254*463	60	H2510-610 20050207
1005-1250	20.0	285*254*390	60	H2010-610 20050207
890-1110	15.0	285*254*317	60	H1510-610 20050207

### CLOSING MECHANISM:

Screw cap	Producer	Drawings	Material	Gasket	Torque
60 mm	KTH GmbH	V 6126-OV	Chevron Phillips Marlex HXM 50100	Foamed PE	20 - 25 Nm
61 mm	Emballator Växjöplast AB	12575, 18.08.15	HDPE, details in report	EPE/PET, EPE/IHS, EPE/ALU	20 - 25 Nm
60 mm	Bergi-Plast GmbH	002-1836	Total 51090	Foamed PE	20 - 25 Nm



### LEGISLATION:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

### REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

### TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

6.1.5.2.6 Chemical compatibility

6.1.5.3 Drop test

6.1.5.4 Leakproofness test

6.1.5.5 Internal pressure test

6.1.5.6 Stacking test

6.1.5.7 Supplementary permeability test

### APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances covered by the liquids listed in the table below. The liquids marked with letter A - F are referring to standard liquids listed in ADR 6.1.6.1 and verified by chemical compatibility testing, ADR 6.1.5.2.6, to this specific liquid.

The dangerous substances allowed to transport in the packaging after chemical compatibility with these liquids, are listed in the "Assimilation list" table 4.1.1.21.6 in ADR.

The packaging shall always be used according to the requirements of the applicable UN-code and its packaging instructions.

Content	Max. gross weight, kg	Max. vapour pressure, kPa at +50°C
Standard liquid A: Wetting Solution	1.2	142
Standard liquid B: Acetic Acid	1.1	142
Standard liquid C: n-Butyl acetate	1.0	142
Standard liquid D: Mixture of hydrocarbons	1.0	142
Standard liquid E: Nitric Acid	1.4	142
Standard liquid F: Water	1.9	142

### DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET0112A	04.10.2007	NET	Type approval
NET0120A	19.01.2011	NET	Type approval
NET16T04	24.01.2016	NET	Additional type test, cap 61 mm

### VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.

### TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001.

The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.



BREVIK, NORWAY

05.01.2022 CERTIFICATE IS VALID UNTIL:

31.01.2027

A handwritten signature in blue ink, reading 'Mathias Werner'.

Mathias Werner  
Certification Officer

A handwritten signature in blue ink, reading 'Rune Madsen Fink'.

Rune Madsen Fink  
Control Officer

*Nordisk Emballasje Testing Certification*

