

PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET7416C

HOLDER OF CERTIFICATE:
Berry Bramlage Kolding A/S

MANUFACTURER: Berry Bramlage Kolding A/S, Gl. Donsvej 12, 6000 Kolding, Denmark

MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 12 mm high. The packaging shall also be appropriately marked with the month of the manufacture.

 **3H1/Y1.5/100/YR/N/NET7416C - ID**

	: The United Nations symbol
3H1	: Plastics jerricans, non-removable head
Y1.5	: Packaging group II and III, and relative density of the substance
100	: Hydraulic test pressure in kPa
YR	: To be replaced with the last two digits of the year of manufacture
N	: Norway, the state authorizing the allocation of the mark
NET7416C - ID	: Identification of the jerrican followed by "ID" to be replaced by the name or symbol of the manufacturer

PRODUCT:

Description

Blow moulded stackable jerrican performed in HDPE, details in report.



DIMENSIONS:

Weight of the jerrican, g	Volume, l	L*W*H, mm	Neck size, mm	Drawing
1050	25.0	295*257*448	61	5225
1050	25.0	295*257*448	55	5225
1100-1250	28.0	298*257*466	61	5228
1100-1250	28.0	298*257*466	55	5228

CLOSING MECHANISM:

#: Screw cap	Producer	Material	Gasket
1: 61 mm	Kunststoff-Technik (KTH).	Marlex HXM 50100 or Lupolen 4261 A	Washer in PE foam Alveocel
2: 61 mm, vented	Kunststoff-Technik (KTH).	Marlex HXM 50100 or Lupolen 4261 A	Washer in PE foam Alveocel
3: 61 mm, OV-HK	Kunststoff-Technik (KTH).	Marlex HXM 50100 or Lupolen 4261 A	Washer in PE foam Alveocel
4: 61 mm	Sabeu (Kunststoff-Werkhe)	Lupolen 4261 A	Washer in EPE 300
5: 61 mm, vented	Sabeu (Kunststoff-Werkhe)	Lupolen 4261 A	Washer in EPE 300
6: 61 mm	RPC UCP Norwich	Total SI 508	Washer in PTFE/EPE 200
7: 61 mm, vented	RPC UCP Norwich	Total SI 508	Washer in PTFE/EPE 200
8: 55 mm	Promens Bjæverskov (Rosti)	Borealis HE 7004	Washer in PE foam Alveocel
9: 61 mm	Kunststoff- Technik (KTH)	Marlex HXM 50100 or Lupolen 4261 A	Washer in PE foam Alveocel

LEGISLATION:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

6.1.5.2.6 Chemical compatibility

6.1.5.3 Drop test

6.1.5.4 Leakproofness test

6.1.5.5 Internal pressure test

6.1.5.6 Stacking test

6.1.5.7 Supplementary permeability test

APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances covered by the liquids listed in the table below. The liquids marked with letter A - F are referring to standard liquids listed in ADR 6.1.6.1 and verified by chemical compatibility testing, ADR 6.1.5.2.6, to this specific liquid.

The dangerous substances allowed to transport in the packaging after chemical compatibility with these liquids, are listed in the "Assimilation list" table 4.1.1.21.6 in ADR.

The packaging shall always be used according to the requirements of the applicable UN-code and its packaging instructions.

Content	Max. relative density	Max. vapour pressure, kPa at +50°C
Standard liquid A: Wetting Solution	1.2	114
Standard liquid B: Acetic Acid	1.1	114
Standard liquid C: n-Butyl acetate	1.0	114
Standard liquid D: Mixture of hydrocarbons	1.0	114
Standard liquid E: Nitric Acid	1.4	114
Standard liquid F: Water	1.5	114

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET7416CZ	17.03.2022	NET	Type approval

VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001.

The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.



BREVIK, NORWAY

17.03.2022 CERTIFICATE IS VALID UNTIL:

31.03.2027


A handwritten signature in blue ink, reading 'Geir M. Johansen'.

Geir Morten Johansen
Certification Officer

A handwritten signature in blue ink, reading 'Rune Madsen Fink'.

Rune Madsen Fink
Control Officer

Nordisk Emballasje Testing Certification

A large, faint, light blue background logo in the center of the page, resembling a stylized umbrella or a shield with a cross-like shape in the middle.