

PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET120202A

HOLDER OF CERTIFICATE:

AS Tehnoplast

MANUFACTURER: AS Tehnoplast, Laki 5A, 10621 Tallin , Estonia

MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 6 mm high. The packaging shall also be appropriately marked with the month of the manufacture.

(n) 3H1/Y1.2/120/YR/N/NET120202A - ID

 $\binom{\mathsf{u}}{\mathsf{n}}$: The United Nations symbol

3H1 : Plastics jerricans, non-removable head

Y1.2 : Packaging group II and III, and relativ density of the substance

120 : Hydraulic test pressure in kPa

YR : To be replaced with the last two digits of the year of manufacture

N : Norway, the state authorizing the allocation of the mark

NET120202A - ID : Identification of the jerrican followed by "ID" to be replaced by the name or symbol of the manufacturer

PRODUCT:

Description

Blow moulded stackable jerrican performed in HDPE, details in report.



DIMENSIONS:

Weight of the	Volume, I	L*W*H/ Neck size,	Min. wall thickness,	Drawing
veight of the	volume, i	L W 11/ Neck Size,	Mill. Wall trickless,	Drawing
jerrican, g		mm	mm	
416.8-439.9	10.0	235*190*330/ 40	0.68	Kanister 10 L
				17.09.2020

MAXIMUM DEGREE OF FILLING IN LITER AT 15 °C, SHALL BE:

Initial boiling	< 60	>= 60 < 100	>= 100 < 200	>= 200 < 300	>= 300
point in °C					
10 l jerrican	10.6	10.8	11.1	11.3	11.6

Telephone +47 900 17025

E-mail: <u>info@net17025.com</u>

Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E



CLOSING MECHANISM:

Screw cap	Producer	Drawing	Material	Gasket	Torque
40 mm	AS Tehnoplast	40F-LINER	HDPE, details in	Wad, PET/	5 Nm
			report	ALKOzell/ PET	



LEGISLATION:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

6.1.5.2.6 Chemical compatibility

6.1.5.3 Drop test

6.1.5.4 Leakproofness test

6.1.5.5 Internal pressure test

6.1.5.6 Stacking test

Telephone +47 900 17025
E-mail: info@net17025.com
Web: www.net17025.com

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E



APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances covered by the liquids listed in the table below. The liquids marked with letter A - F are referring to standard liquids listed in ADR 6.1.6.1 and verified by chemical compatibility testing, ADR 6.1.5.2.6, to this specific liquid.

The dangerous substances allowed to transport in the packaging after chemical compatibility with these liquids, are listed in the "Assimilation list" table 4.1.1.21.6 in ADR.

The packaging shall always be used according to the requirements of the applicable UN-code and its

packaging instructions.

Content	Max. gross weight, kg	Max. vapour pressure, kPa at
		+50°C
Standard liquid B: Acetic Acid	1.1	125.7

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET120202A	27.07.2022	NET	Type approval

VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.

NORSK AKKREDITERING TEST 259

BREVIK, NORWAY

27.07.2022 CERTIFICATE IS VALID UNTIL:

31.07.2027

Mathias Werner Certification Officer Rune Madsen Fink Control Officer

Nordisk Emballasje Testing Certification

Muis Wemer

Telephone +47 900 17025
E-mail: info@net17025.com
Web: www.net17025.com

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E