

TYPE APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET0345B

HOLDER OF CERTIFICATE: Greif Sweden AB

MANUFACTURER:

Greif Sweden AB, Kvekatorpsvägen 25, Box 203, SE-311 23 Falkenberg, Sweden

MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 12 mm high.

(^u) 1A2/Y1.5 Z1.9/100/YR/N/NET0345B - ID

(u)	: The United Nations symbol
1A2	: Steel drums, removable head
Y1.5 Z1.9	: Packaging group II and III, and max relative density
100	: Hydraulic test pressure in kPa
YR	: To be replaced with the year (last two digits) of manufacture
Ν	: Norway, the state authorizing the allocation of the mark
NET0345B - ID	: Identification of the packaging followed by "ID" to be replaced by the name of the manufacturer

PRODUCT:

Description	Method of manufacture		Material		Drawing	
Triple seamed neck in	Seamed		Steel	DC01		F3P-2791 Rev.B
corrugated W hoop drum						



DIMENSIONS:

Volume, l	H*Ø, mm	Head/ Body/ Bottom, mm
210	866*582 1.0/ 0.9/ 1.0	

MAXIMUM DEGREE OF FILLING IN LITER AT 15 °C, SHALL BE:

Initial boiling	< 60	>= 60 < 100	>= 100 < 200	>= 200 < 300	>= 300
point in °C					
Degree of filling	191.5	195.7	200.0	204.2	208.5
in liter					

NET0345B Page 1 of 4

IE10343D	Page 1 01 4
Telephone	+47 900 17025
E-mail:	info@net17025.com
Web:	www.net17025.com



CLOSING MECHANISM:

Closure type	Drawings	Material	Gasket	Torque
Clamping ring with	amping ring with A4F-2674 270103 DX51D+Z100		-	-
lever arm				
Clamping ring with	1018-22 070415	DX51D+ Z	-	-
lever arm				
Clamping ring with	CLRI00193GGG000	DX51D+ Z	-	-
lever arm				
Plain lid	D3F-2595 Rev. B	DC01	EPDM 12 mm	-
Lid with 2" bung	D3F-2595 Rev. B	DC01	EPDM 12 mm	-
Lid with 2" and 3/4"	D3F-2595 Rev. B	DC01	EPDM 12 mm	-
bung				
3/4" bung	TSN-925096	Zinc-plated Mild	EPDM / PE / Nitrile	15
		steel		
2" umbrella	TSN-939324	Zinc-plated Mild	EPDM / PE / Nitrile	20
vent-out		steel		
2" umbrella vent-in	TSN-939323	Zinc-plated Mild	EPDM / PE / Nitrile	20
		steel		
2"	TSN 925089	Zinc-plated Mild	EPDM / PE / Nitrile	20
		steel		















LEGISLATION:

NET issues the certification on described product according to delegated authority from Norwegian NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 2023/4375 PRAX.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

- 6.1.5.3 Drop test
- 6.1.5.4 Leakproofness test
- 6.1.5.5 Internal hydraulic pressure test
- 6.1.5.6 Stacking test

APPROVAL IS VALID FOR:

The packaging shall always be used according to the requirement of the applicable UN-code and its packaging instruction.

Content	Max. vapour pressure, kPa at +50°C
Liquid substances that do not adversely affect the	114
packaging materials	

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET0345B	31.03.2014	NET	Type approval
NET0345B1	04.11.2014	NET	Type approval
NET0345B3	12.03.2015	NET	Selective testing
NET0345B4	27.03.2023	NET	Additional type test, ring



VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.

TEST STANDARD:

BREVIK, NORWAY

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495.



31.05.2028

Amis Weme-

Mathias Werner Certification Officer

Nordisk Emballasje Testing Certification

Rune Madsen Fink Control Officer

24.05.2023 CERTIFICATE IS VALID UNTIL: