

# TYPE APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET0340A

# HOLDER OF CERTIFICATE: Greif Sweden AB

### MANUFACTURER:

Greif Sweden AB, Kvekatorpsvägen 25, Box 203, SE-311 23 Falkenberg, Sweden

### MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 12 mm high.

### (") 1A2/Y242/S/YR/N/NET0340A - ID

| (u)<br>n      | : Т | he United Nations symbol           |               |  |
|---------------|-----|------------------------------------|---------------|--|
| 1A2           | : 5 | Steel drums, removable head        |               |  |
| Y242          | : P | ackaging group II and III, and m   | nax gross we  | ight in kg                                       |
| S             | : I | ntended for carriage of solids     |               |  |
| YR            | : T | o be replaced with the year (last  | two digits)   | of manufacture                                   |
| Ν             | : N | lorway, the state authorizing the  | allocation of | f the mark                                       |
| NET0340A - ID | : I | dentification of the packaging fol | lowed by "ID  | " to be replaced by the name of the manufacturer |

#### **PRODUCT:**

| Description            | Method of manufacture |  | Material |      | Drawing          |
|------------------------|-----------------------|--|----------|------|------------------|
| Triple seamed straight | Seamed                |  | Steel    | DC01 | HE3F-2679 Rev. B |
| drum                   |                       |  |          |      |                  |



#### **DIMENSIONS:**

| Volume, l | H*Ø, mm | Head/ Body/ Bottom, mm |
|-----------|---------|------------------------|
| 210       | 877*595 | 1.0/ 0.8/ 1.0          |

#### MAXIMUM DEGREE OF FILLING IN LITER AT 15 °C, SHALL BE:

| Initial boiling   | < 60  | >= 60 < 100 | >= 100 < 200 | >= 200 < 300 | >= 300 |
|-------------------|-------|-------------|--------------|--------------|--------|
| point in °C       |       |             |              |              |        |
| Degree of filling | 193.1 | 197.4       | 201.7        | 206.0        | 210.3  |
| in liter          |       |             |              |              |        |

# NET0340A Page 1 of 4

|           | ruge I or 4       |
|-----------|-------------------|
| Telephone | +47 900 17025     |
| E-mail:   | info@net17025.com |
| Web:      | www.net17025.com  |
|           |                   |



## **CLOSING MECHANISM:**

| Closure type                       | Drawings        | Material         | Gasket              | Torque |
|------------------------------------|-----------------|------------------|---------------------|--------|
| Clamping ring with A4F-2674 270103 |                 | DX51D+Z100       | -                   | -      |
| lever arm                          |                 |                  |                     |        |
| Clamping ring with                 | 1018-22 070415  | DX51D+ Z         | -                   | -      |
| lever arm                          |                 |                  |                     |        |
| Clamping ring with                 | CLRI00116GGG000 | DX51D+ Z         | -                   | -      |
| lever arm                          | 1               |                  |                     |        |
| Plain lid                          | D3F-2595 Rev. B | DC01             | PVC or EPDM 7 or 9  | -      |
|                                    |                 |                  | mm                  |        |
| Lid with 2" bung                   | D3F-2595 Rev. B | DC01             | PVC or EPDM 7 or 9  | -      |
|                                    |                 |                  | mm                  |        |
| Lid with 2" and 3/4"               | D3F-2595 Rev. B | DC01             | PVC or EPDM 7 or 9  | -      |
| bung                               |                 |                  | mm                  |        |
| 3/4" bung                          | TSN-925096      | Zinc-plated Mild | EPDM / PE / Nitrile | 15     |
|                                    |                 | steel            |                     |        |
| 2" umbrella                        | TSN-939324      | Zinc-plated Mild | EPDM / PE / Nitrile | 20     |
| vent-out                           |                 | steel            |                     |        |
| 2" umbrella vent-in                | TSN-939323      | Zinc-plated Mild | EPDM / PE / Nitrile | 20     |
|                                    |                 | steel            |                     |        |
| 2"                                 | TSN 925089      | Zinc-plated Mild | EPDM / PE / Nitrile | 20     |
|                                    |                 | steel            |                     |        |













#### LEGISLATION:

NET issues the certification on described product according to delegated authority from Norwegian NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 2023/4375 PRAX.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

### **REGULATIONS BASED UPON FOR APPROVAL:**

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

#### **TESTS CARRIED OUT:**

Prototype tests performed and approved according to the above regulations: 6.1.5.3 Drop test 6.1.5.6 Stacking test

#### **J**

## **APPROVAL IS VALID FOR:**

The packaging shall always be used according to the requirement of the applicable UN-code and its packaging instruction.

#### Content

Solid substances that do not adversely affect the packaging materials

#### **DOCUMENTS BASED UPON FOR APPROVAL:**

| Report id. | Date       | Issued by | Scope                      |
|------------|------------|-----------|----------------------------|
| F408248    | 15.04.2004 | SP        | Type testing and           |
|            |            |           | technical evaluation       |
| NET03TE10  | 30.06.2011 | NET       | Technical evaluation       |
| NET03T14   | 08.12.2011 | NET       | Type testing               |
| NET03TE19  | 02.12.2014 | NET       | Technical evaluation       |
| NET0339A3  | 27.03.2023 | NET       | Additional type test, ring |
|            |            |           | straight                   |

#### VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.



#### INTERNATIONAL CERTIFICATE

#### **TEST STANDARD:**

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495.



31.05.2028

BREVIK, NORWAY

Mathias Werner

**Certification Officer** 

28.08.2023 CERTIFICATE IS VALID UNTIL:

Marmis Weme-

Rune Madsen Fink Control Officer

Nordisk Emballasje Testing Certification