

TYPE APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NETO213D

HOLDER OF CERTIFICATE:

Berry Norway Containers AS

MANUFACTURER: Berry Norway Containers AS, Kambo, Brevikveien 535, N-1506

Moss, Norway

MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 6 mm high. The packaging shall also be appropriately marked with the month of the manufacture.

(h) 3H1/Y1.9/100/YR/N/NET0213D - ID

 $\binom{\mathsf{u}}{\mathsf{n}}$: The United Nations symbol

3H1 : Plastics jerricans, non-removable head

Y1.9 : Packaging group II and III, and relative density of the substance

100 : Hydraulic test pressure in kPa

YR : To be replaced with the last two digits of the year of manufacture

N : Norway, the state authorizing the allocation of the mark

NET0213D - ID : Identification of the jerrican followed by "ID" to be replaced by the name or symbol of the manufacturer

PRODUCT:

Description/ Method of manufacture

Blow moulded jerrican performed in HDPE, details in report.



DIMENSIONS:

Weight of the	Volume, I	L*W*H, mm	Neck size, mm	Min. wall	Drawing,
jerrican, g				thickness, mm	Product
1: 237 - 252	5.0	189.1 * 125.9 *	40	0.59	B-30926
		320.0			
2: 175 - 183	3.0	189.1 * 125.9 *	40	0.59	B-30953
		228.0			

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E



CLOSING MECHANISM:

Screw cap	Producer	Drawings	Material	Gasket	Torque, Nm
40 mm CRC	Modulpac AB	8400003	HDPE, details in	PET/ PE/	8 Nm
			report	foamed EPE/	
				PE/ solid PET	



LEGISLATION:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

6.1.5.2.6 Chemical compatibility

6.1.5.3 Drop test

6.1.5.4 Leakproofness test

6.1.5.5 Internal pressure test

6.1.5.6 Stacking test

6.1.5.7 Supplementary permeability test

NET0213D Page 2 of 3

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E



APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances covered by the liquids listed in the table below. The liquids marked with letter A - F are referring to standard liquids listed in ADR 6.1.6.1 and verified by chemical compatibility testing, ADR 6.1.5.2.6, to this specific liquid.

The dangerous substances allowed to transport in the packaging after chemical compatibility with these liquids, are listed in the "Assimilation list" table 4.1.1.21.6 in ADR.

The packaging shall always be used according to the requirements of the applicable UN-code and its

packaging instructions.

<u></u>				
Content	Max. relative density	Max. vapour pressure, kPa at		
		+50°C		
Standard liquid D: Mixture of	1.0	114		
hydrocarbons				
Standard liquid F: Water	1.9	114		

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET0213A	22.01.2013	NET	Type approval
NET2811A	16.06.2019	NET	Additional type test cap
NET2825A	23.03.2021	NET	Additional type test cap

VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.



BREVIK, NORWAY

02.11.2023 CERTIFICATE IS VALID UNTIL:

31.03.2025

Geir Morten Johansen Certification Officer

laci His loho

Rune Madsen Fink Control Officer

Nordisk Emballasje Testing Certification

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E