

**TYPE APPROVAL OF PACKAGING FOR
TRANSPORTATION OF DANGEROUS GOODS
CERTIFICATE NO.: NET17801A**

HOLDER OF CERTIFICATE:
Chemring Nobel AS

4312 kg max

MANUFACTURER:

Bison IBC Ltd, Burma Road, Blidworth Industrial Park,
NG21 0RT Blidworth, Great Britain



MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 12 mm high. The IBC shall also be appropriately marked in accordance with ADR 6.5.2.2 Additional marking, and shall be marked with maximum permitted stacking load according to ADR 6.5.2.2.2.1 (as shown in figure to left).

UN 31A/Y/MMYY/N/NET17801A - BC/7762/2156

- UN** : The United Nations symbol
- 31A** : Steel IBCs for liquids
- Y** : Packaging group II and III
- MMYY** : To be replaced with the month and year (last two digits) of manufacture
- N** : Norway, the state authorizing the allocation of the mark
- NET17801A - ID** : Identification of the IBC followed by "ID" to be replaced by the name or symbol of the manufacturer
- 7236** : The stacking test load in kg
- 2156** : The maximum permissible gross mass in kg

PRODUCT:

Method of manufacture/ Description

The IBC is welded in Stainless Steel L 316. It is UN certified for transportation and storage of liquids up to a density of 1.9 s.g. It has a standard pallet footprint of 1200 x 1000 mm and can be stacked three high full.



DIMENSIONS:

Capacity, l	External dimensions: L*W*H, mm	Head / Body / Bottom, mm	Drawing
1000	1195*990*1420	2.0 / 2.0 / 2.0	DRPH041223-A

MAXIMUM DEGREE OF FILLING IN LITER AT 15 °C, SHALL BE:

Initial boiling point in °C	< 60	>= 60 < 100	>= 100 < 200	>= 200 < 300	>= 300
Degree of filling in liter	962	983	1005	1026	1048

CLOSING MECHANISM:

Closure type	Producer	Drawings	Material	Gasket
Lid	Bison	DRPH041223-L	L 316	Densiq Art.no: 99000116950000
Clamping ring with lever arm	Bison	DRPH041223-C	L 316	-
3/4" bung	Any	-	L 316	-

LEGISLATION:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 2023/4375 PRAX.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

6.5.6.4 Bottom lift test

6.5.6.5 Top lift test: WLL 539 kg, all 4 padeyes shall be used when lifting the IBC

6.5.6.6 Stacking test

6.5.6.7 Leakprooiness test

6.5.6.8 Internal pressure test

6.5.6.9 Drop test

6.5.6.13 Vibration test

APPROVAL IS VALID FOR:

Transport of liquids in this IBC is allowed as long as a conventional pressure relief device is mounted. The start-to-discharge pressure shall not be higher than 65 kPa and not lower than the total gauge pressure experienced in the IBC. The IBC shall always be used according to the requirement of the applicable UN-code and its packaging instruction.

Content	Max. relative density	Pressure test, kPa
Liquids that do not adversely affect the packaging materials	1.9	200

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET17801A	01.12.2023	NET	Type approval

VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495.



BREVIK, NORWAY

18.12.2023

CERTIFICATE IS VALID UNTIL:

31.12.2028

Mathias Werner
Certification Officer



Rune Madsen Fink
Control Officer

Nordisk Emballasje Testing Certification