VAT No.: 990 793 840

Bank account: 6250.05.22351

GPS: 59°03'25" N 9°40'70" E



TYPE APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NETO366C

HOLDER OF CERTIFICATE: **Greif Sweden AB**

MANUFACTURER: Greif Sweden AB, Kvekatorpsvägen 25, Box 203, SE-311 23

Falkenberg, Sweden

MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 12 mm high. The packaging shall also be appropriately marked with the month of the manufacture. The period of use permitted for the carriage of dangerous substances shall be five years from the date of manufacture of the jerricans, except where a shorter period of use is prescribed because of the nature of the substance to be carried.

(h) 3H1/Y1.9/200/YR/N/NET0366C - ID

(u) : The United Nations symbol

3H1 : Plastics jerricans, non-removable head

Y1.9 : Packaging group II and III, and relative density of the substance

200 : Hydraulic test pressure in kPa

YR : To be replaced with the last two digits of the year of manufacture

N : Norway, the state authorizing the allocation of the mark

NET0366C - ID : Identification of the jerrican followed by "ID" to be replaced by the name or symbol of the manufacturer

PRODUCT:

Method of manufacture/ Description/ Min. wall thickness

Blow moulded stackable jerrican performed in HDPE, details in report.



DIMENSIONS:

DIFICIONS:					
Weight of the	Volume, I	L*W*H, mm	Neck size, mm	Drawing	
jerrican, g					
1: 930-1388	20.0	295*260*376	60	FB-0021 Rev B,	
				FB-0001 Rev B	
2: 980-1388	20.0	295*260*376	60	FB-0021 Rev B,	
				FB-0001 Rev B	

E-mail: info@net17025.com

Web: www.net17025.com





3: 1078-1132	20.0	295*260*376	60	FB-0021 Rev B,
				FB-0001 Rev B
4: 1071-1598	25.0	295*260*441	60	FB-0022 Rev B,
				FB-0002 Rev B
5: 1127-1598	25.0	295*260*441	60	FB-0022 Rev B,
				FB-0002 Rev B
6: 1240-1302	25.0	295*260*441	60	FB-0022 Rev B,
				FB-0002 Rev B
7: 1124-1676	27.5	295*260*470	60	FB-0023 Rev B,
				FB-0003 Rev B

MAXIMUM DEGREE OF FILLING IN LITER AT 15 °C, SHALL BE:

Initial boiling < 60 >= 60 < 100 >= 100 < 200 >= 200 < 300 >= 300						
point in °C	. 00	00 1 100	100 (200	200 (300	, 300	
•						
Degree of filling	25.11	25.7 l	26.2 l	26.8 I	27.3 l	

CLOSING MECHANISM:

#: Screw cap	Producer	Drawings	Material	Gasket	Torque
1: 60 mm	Tri-Sure	TSF-504224-2	HDPE, details in	Washer,	25 Nm
			report	expanded PE	
2: 60 mm	Tri-Sure	F4P-2015	HDPE, details in	Wad, expanded	25 Nm
			report	PE	
3: 60 mm	Tri-Sure	F4P-2015	HDPE, details in	Washer,	25 Nm
			report	expanded PE	
4: Vented 60	Tri-Sure	TSF-504351-2	HDPE, details in	Washer,	25 Nm
mm			report	expanded PE	
5: 60 mm	Bergi-Plast	00-1836	HDPE, details in	Washer, EPE	25 Nm
	GmbH		report	300	
7: 60 mm	Kunststoff-techn	KTH55-SK61-1	HDPE, details in	Washer,	25 Nm
	ik		report	expanded PE	
8: 60 mm	United caps	09S41LB13-01	HDPE, details in	Wad, induction	25 Nm
			report	liner	
9: 25 mm	Modulpac AB	25PMPP REV 3	HDPE, details in	Wad, PET/	3 Nm
			report	Alkozell/ PET	
10: 60 mm	United caps	BV0600C B	HDPE, details in	Wad, Alu30my/	25 Nm
			report	PET12my/	
				PE60my	
11: Vented 60	Tri-Sure	TSF-505512-1	HDPE, details in	Washer,	25 Nm
mm			report	expanded PE	
12: 60 mm	Tri-Sure	TSF-506492	HDPE, details in	Washer,	25 Nm
Carbon black			report	expanded PE	
free					

 NET0366C
 Page 2 of 6

 Telephone
 +47 900 17025

 E-mail:
 info@net17025.com
 Web: www.net17025.com







 NET0366C
 Page 3 of 6

 Telephone
 +47 900 17025

 E-mail:
 info@net17025.com

 Web:
 www.net17025.com





LEGISLATION:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 2023/4375 PRAX.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

6.1.5.2.6 Chemical compatibility

6.1.5.3 Drop test

6.1.5.4 Leakproofness test

6.1.5.5 Internal pressure test

6.1.5.6 Stacking test

6.1.5.7 Supplementary permeability test

NET0366C Page 4 of 6

NET Emballasje- og Produkttesting AS T Blekebakkvegen 45 N-3950 Brevik

Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>



APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances covered by the liquids listed in the table below. The liquids marked with letter A - F are referring to standard liquids listed in ADR 6.1.6.1 and verified by chemical compatibility testing, ADR 6.1.5.2.6, to this specific liquid.

The dangerous substances allowed to transport in the packaging after chemical compatibility with these liquids, are listed in the "Assimilation list" table 4.1.1.21.6 in ADR. Transport of the substance is only allowed if the approval of the standard liquid(S), covered by "Rule for collective entries", has the same or higher relative density as the substance to be transported.

The packaging shall always be used according to the requirements of the applicable UN-code and its packaging instructions.

Content	Max. relative density	Packaging #	Screw cap #
Standard liquid A:	1.2	All items	All items
Wetting Solution			
Standard liquid A:	1.4	3 & 6	1, 12 & 9
Wetting Solution			
Standard liquid B: Acetic	1.2	All items	All items
Acid			
Standard liquid B: Acetic	1.4	3 & 6	1, 12 & 9
Acid			
Standard liquid C:	1.0	All items	All items
n-Butyl acetate			
Standard liquid D:	1.0	All items	All items
Mixture of hydrocarbons			
Standard liquid D:	1.4	3 & 6	1, 12 & 9
Mixture of hydrocarbons			
Standard liquid E: Nitric	1.4	2 & 5	1-7, 9 & 11
Acid			
Standard liquid F: Water	1.9	All items	All items
Nitric acid 55 - 62%	1.4	2 & 5	5,7 & 9

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET0356C	22.06.2016	NET	Type approval
NET0356C2	08.08.2016	NET	Additional test, MoH
NET0356D	22.06.2016	NET	Type approval
NET0356D2	08.08.2016	NET	Additional type test,
			MoH, n-Ba
NET03TE28	02.09.2016	NET	Calculation of production
			weights
NET03TE29	02.09.2016	NET	Technical evaluation,
			pallet
NET0356D3	11.10.2016	NET	Additional type test,
			MoH, Ws
NET0356D4-K	24.11.2016	NET	Additional type test, cap
			3 & 9
NET0356D5	31.01.2017	NET	Additional type test, MoH
			anti-glug

Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>





NET0366C2	21.10.2019	NET	Additional type test, Na
			62%
NET03TE42	01.06.2021	NET	Technical evaluation
NET0366C3	19.09.2023	NET	Additional type test,
			increast density
NET0366C4	21.02.2024	NET	Additional type test,
			increast density

VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.

NORSK AKKREDITERING TEST 259

BREVIK, NORWAY

27.02.2024 CERTIFICATE IS VALID UNTIL:

Rune Madsen Fink

Control Officer

28.02.2029

Mathias Werner Certification Officer

Nordisk Emballasje Testing Certification

Mis Weme

NET0366C Page 6 of 6

NET Emballasje- og Produkttesting AS Blekebakkvegen 45 N-3950 Brevik Telephone +47 900 17025
E-mail: info@net17025.com
Web: www.net17025.com