

# TYPE APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET3101A

# HOLDER OF CERTIFICATE:

# Norsk Formblåsing AS

MANUFACTURER: Norsk Formblåsing AS, Merdeveien 12 B, 3676 Notodden, Norway

## **MARKING ON PACKAGING:**

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 6 mm high. The packaging shall also be appropriately marked with the month of the manufacture. The period of use permitted for the carriage of dangerous substances shall be five years from the date of manufacture of the jerricans, except where a shorter period of use is prescribed because of the nature of the substance to be carried.

# (n) 3H1/Y1.9/100/YR/N/NET3101A - ID

(u) : The United Nations symbol

3H1 : Plastics jerricans, non-removable head

Y1.9 : Packaging group II and III, and relative density of the substance

100 : Hydraulic test pressure in kPa

YR : To be replaced with the last two digits of the year of manufacture

N : Norway, the state authorizing the allocation of the mark

NET3101A - ID : Identification of the jerrican followed by "ID" to be replaced by the name or symbol of the manufacturer

# **PRODUCT:**

Description/ Method of manufacture/ Min. wall thickness

4 L, none-stackable jerrican performed in HDPE, details in report/ Blow moulded/ 0.65 mm



#### **DIMENSIONS:**

Weight of the	Volume, I	L*W*H, mm	Neck size, mm	Drawing
jerrican, g				
222.6-239.8	4.0	158*120*319	39.6	4L kanne med ny
				hals og skulder,
				170914

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E



## MAXIMUM DEGREE OF FILLING IN LITER AT 15 °C, SHALL BE:

Initial boiling	< 60	>= 60 < 100	>= 100 < 200	>= 200 < 300	>= 300
point in °C					
Degree of filling	3.6	3.7	3.8	3.9	4.0
in liter					

#### **CLOSING MECHANISM:**

0_00_110_11_011111101111						
Producer	Drawings	Material	Gasket	Torque		
Modulpac AB	7400005/	DOW KT 10000	Top-seals PHAN	5 Nm		
	7400016	UE/ Marlex	200			
		HHM5502-01ST				
Emballator	12445	Borealis	EPE/ PET	5 Nm		
Växjö AB		MB7541				
	Modulpac AB Emballator	Modulpac AB 7400005/ 7400016 Emballator 12445	Modulpac AB 7400005/ 7400016 DOW KT 10000 UE/ Marlex HHM5502-01ST Emballator 12445 Borealis	Modulpac AB         7400005/ 7400016         DOW KT 10000 UE/ Marlex HHM5502-01ST         Top-seals PHAN 200           Emballator         12445         Borealis         EPE/ PET		





#### **LEGISLATION:**

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 2023/4375 PRAX.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

## **REGULATIONS BASED UPON FOR APPROVAL:**

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

NET3101A Page 2 of 4

Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E



#### **TESTS CARRIED OUT:**

Prototype tests performed and approved according to the above regulations:

6.1.5.2.6 Chemical compatibility

6.1.5.3 Drop test

6.1.5.4 Leakproofness test

6.1.5.5 Internal pressure test

6.1.5.6 Stacking test

6.1.5.7 Supplementary permeability test

#### **APPROVAL IS VALID FOR:**

The packaging is valid for packaging group II and III containing liquid substances covered by the liquids listed in the table below. The liquids marked with letter A - F are referring to standard liquids listed in ADR 6.1.6.1 and verified by chemical compatibility testing, ADR 6.1.5.2.6, to this specific liquid.

The dangerous substances allowed to transport in the packaging after chemical compatibility with these liquids, are listed in the "Assimilation list" table 4.1.1.21.6 in ADR. Transport of the substance is only allowed if the approval of the standard liquid(S), covered by "Rule for collective entries", has the same or higher relative density as the substance to be transported.

The packaging shall always be used according to the requirements of the applicable UN-code and its

packaging instructions.

p at a transfer of the at a tr				
Content	Max. relative density		Max. vapour pressure, kPa at	
			+50°C	
Standard liquid: Jotun	1.1		114	
Kraftvask,UN1760				
Standard liquid: Mixture of	1.0		114	
hydrocarbons				
Standard liquid: Water	1.9		114	

#### **DOCUMENTS BASED UPON FOR APPROVAL:**

Report id.	Date	Issued by	Scope	
NET3101A2	13.07.2016	NET	Type test	
NET3101A4-2	13.06.2017	NET	Type test	
NET3101A5	16.04.2018	NET	Type test	
NET3101A10	01.08.2018	NET	Additional type test,	
			MoH, W	

# **VALIDITY:**

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in NS-EN ISO 16106:2020.

Telephone +47 900 17025 VAT No.: 990 793 840
E-mail: info@net17025.com Bank account: 6250.05.22351
Web: www.net17025.com GPS: 59°03'25" N 9°40'70" E





## **TEST STANDARD:**

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with NS-EN ISO/IEC 17025:2017 approved by Norsk Akkreditering and according to NS-EN ISO 16495:2022 and NS-EN ISO 13274:2013.



BREVIK, NORWAY

**14.02.2024** CERTIFICATE IS VALID UNTIL:

Control Officer

30.09.2028

Mathias Werner Certification Officer

Nordisk Emballasje Testing Certification

Aluis Wemen

NET3101A Page 4 of 4

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E