

TYPE APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET0369C

HOLDER OF CERTIFICATE: Greif Sweden AB

MANUFACTURER:

Greif Sweden AB, Kvekatorpsvägen 25, Box 203, SE-311 23 Falkenberg, Sweden

MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 6 mm high. The packaging shall also be appropriately marked with the month of the manufacture. The period of use permitted for the carriage of dangerous substances shall be five years from the date of manufacture of the jerricans, except where a shorter period of use is prescribed because of the nature of the substance to be carried.

(^u) 3H1/Y1.2/130/YR/N/NET0369C - ID

(un)	: The United Nations symbol
3H1	: Plastics jerricans, non-removable head
Y1.2	: Packaging group II and III, and max relative density of the substance
130	: Hydraulic test pressure in kPa
YR	: To be replaced with the last two digits of the year of manufacture
N	: Norway, the state authorizing the allocation of the mark
NET0369C	: Identification of the jerrican

PRODUCT:

Method of manufacture/ Description/ Min. wall thickness Blow moulded stackable jerrican performed in HDPE, details in report./ 1.25



DIMENSIONS:

We	ight of the	Volume, l	L*W*H, mm	Neck size, mm	Drawing	
jerr	rican, g					
794	4.1 - 843.5	20.0	290*232*410	60	W3710 - 100925.	
					rev. B	

	NET0369C	Page 1 of 4	
NET AS	Telephone	+47 900 17025	VAT No.: 990 793 840
Blekebakkvegen 45	E-mail:	info@net17025.com	Bank account: 6250.05.22351
N-3950 Brevik	Web:	www.net17025.com	GPS: 59°03'25" N 9°40'70" E



MAXIMUM DEGREE OF FILLING IN LITER AT 15 °C, SHALL BE:

Initial boiling	< 60	>= 60 < 100	>= 100 < 200	>= 200 < 300	>= 300
point in °C					
Degree of filling	20.0	20.4	20.8	21.3	21.7
in liter					

CLOSING MECHANISM:

#: Screw cap	Producer	Drawings	Material	Gasket	Torque
1: 60 mm	Bericap GmbH	ENG-00-100890	HDPE, details in	Washer, PE	19 Nm
		A	report	foam	
2: 60 mm	Tri-Sure	TSF-506527	HDPE, details in	Washer, PE	19 Nm
			report	foam	





LEGISLATION:

The approval is valid for a maximum of five years, provided no modifications are made to the packaging design, materials, dimensions, closure system, or construction method. This certificate may be revoked at any time. To ensure its validity, please check the published version online (www.net17025.com/Sertifisering/UN_ADR/cid/30758/).

NET issues this certification for the described product under delegated authority from the Norwegian Directorate for Civil Protection (DSB), in accordance with the Legal Regulations for the Transportation of Dangerous Goods by road and railway - 2023/4375 PRAX.

NET issues this certification for the described product under delegated authority from the Norwegian Maritime Authority (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues this certification for the described product based on an agreement with the Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

- 6.1.5.2.6 Chemical compatibility
- 6.1.5.3 Drop test
- 6.1.5.4 Leakproofness test
- 6.1.5.5 Internal pressure test
- 6.1.5.6 Stacking test
- 6.1.5.7 Supplementary permeability test

NET AS	
Blekebakkvegen	45
N-3950 Brevik	

NET0369C Page 2 of 4

Telephone	+47 900 17025
E-mail:	info@net17025.com
Web:	www.net17025.com



APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances covered by the liquids listed in the table below. The liquids marked with letter A - F are referring to standard liquids listed in ADR 6.1.6.1 and verified by chemical compatibility testing, ADR 6.1.5.2.6, to this specific liquid.

The dangerous substances allowed to transport in the packaging after chemical compatibility with these liquids, are listed in the "Assimilation list" table 4.1.1.21.6 in ADR. Transport of the substance is only allowed if the approval of the standard liquid(S), covered by "Rule for collective entries", has the same or higher relative density as the substance to be transported.

The packaging shall always be used according to the requirements of the applicable UN-code and its packaging instructions.

Content	Max. relative density	Max. vapour pressure, kPa at +50°C
Standard liquid D: Mixture of	1.2	131
hydrocarbons		
Standard liquid F: Water	1.2	131

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET0369C	25.12.24	NET	Type approval
NET0369B	25.12.24	NET	Type approval, Alt. cap
			design

VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in NS-EN ISO 16106:2020.

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with NS-EN ISO/IEC 17025:2017 approved by Norsk Akkreditering and according to NS-EN ISO 16495:2022 and NS-EN ISO 13274:2013.





INTERNATIONAL CERTIFICATE

BREVIK, NORWAY

13.02.2025 CERTIFICATE IS VALID UNTIL: **31.12.2029**

laci M. Johan

Geir Morten Johansen Certification Officer

Rune Fuck

Rune Madsen Fink Control Officer

Nordisk Emballasje Testing Certification



	NET0369C	Page 4 of 4	
NET AS	Telephone	+47 900 17025	VAT No.: 990 793 840
Blekebakkvegen 45	E-mail:	info@net17025.com	Bank account: 6250.05.22351
N-3950 Brevik	Web:	www.net17025.com	GPS: 59°03'25" N 9°40'70" E