

# TYPE APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET0250C

HOLDER OF CERTIFICATE:  
**Berry Norway Containers AS**

**MANUFACTURER:** Berry Norway Containers AS, Brevikveien 535, N-1506 Moss, Norway

## MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 12 mm high. The packaging shall also be appropriately marked with the month of the manufacture. The period of use permitted for the carriage of dangerous substances shall be five years from the date of manufacture of the jerricans, except where a shorter period of use is prescribed because of the nature of the substance to be carried.

③ **3H1/Y1.4/200/YR/N/NET0250C - ID**

③	: The United Nations symbol
3H1	: Plastics jerricans, non-removable head
Y1.4	: Packaging group II and III, and relative density of the substance
200	: Hydraulic test pressure in kPa
YR	: To be replaced with the last two digits of the year of manufacture
N	: Norway, the state authorizing the allocation of the mark
NET0250C - ID	: Identification of the jerrican followed by "ID" to be replaced by the name or symbol of the manufacturer

## PRODUCT:

Description

Blow moulded stackable jerrican performed in HDPE, details in report.



## DIMENSIONS:

Weight of the jerrican, g	Volume, l	L*W*H, mm	Neck size, mm	Min.thickness	Drawing
1344.0-1425.9	25.0	295*260*440	61 / 25	0.91	W3405 Rev.B
1180.0-1251.9	20.0	295*260*370	61 / 25	0.91	W3405 Rev.B

**MAXIMUM DEGREE OF FILLING IN LITER AT 15 °C, SHALL BE:**

Initial boiling point in °C	< 60	> 60 < 100	>= 100 < 200	>= 200 < 300	>= 300
25 l jerrican	24.02	24.55	25.08	25.62	26.15
20 l jerrican	19.02	19.55	20.08	20.62	21.15

**CLOSING MECHANISM:**

#: Closure type	Producer	Drawings	Material	Gasket	Torque
1: Screw cap	Modulpac AB	25PMPP/7250001	HDPE, details in report	PET/ALKOzell/PET	3 Nm
2: Screw cap	Bergi-Plast GmbH	Kanisterverschluss nr. 61 rev 8	HDPE, details in report	EPE liner	20 Nm


**LEGISLATION:**

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 2023/4375 PRAX.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

**REGULATIONS BASED UPON FOR APPROVAL:**

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

**TESTS CARRIED OUT:**

Prototype tests performed and approved according to the above regulations:

6.1.5.2.6 Chemical compatibility

6.1.5.3 Drop test

6.1.5.4 Leakproofness test

6.1.5.5 Internal pressure test

6.1.5.6 Stacking test

**APPROVAL IS VALID FOR:**

The packaging shall always be used according to the requirements of the applicable UN-code and its packaging instructions.

Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	Max. vapour pressure, kPa at +50°C
Nitric Acid 62%, UN2031	114

#### DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET0250C2	22.08.2018	NET	Type approval
NET02TE11	08.08.2018	NET	Technical evaluation, 20 l
NET2812A	17.12.2020	NET	Additional test, 25PMPP

#### VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in ISO 16106.

#### TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.



BREVIK, NORWAY

26.10.2023 CERTIFICATE IS VALID UNTIL:

31.03.2027



Geir Morten Johansen  
Certification Officer



Rune Madsen Fink  
Control Officer

*Nordisk Emballasje Testing Certification*