

TYPE APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NETO335B

HOLDER OF CERTIFICATE: **Greif Sweden AB**

MANUFACTURER: Greif Sweden AB, Kvekatorpsvägen 25, Box 203, SE-311 23

Falkenberg, Sweden

MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 12 mm high.

(n) 1A1/X/250/YR/N/NET0335B - ID

(u) : The United Nations symbol : Steel drum, non-removable head

X : Packaging group I, II and III, and max relative density 1.2

250 : Hydraulic test pressure in kPa

YR : To be replaced with the year (last two digits) of manufacture
N : Norway, the state authorizing the allocation of the mark

NET0335B - ID : Identification of the drum followed by "ID" to be replaced by the name of the manufacturer

PRODUCT:

Description	Drawing
Triple seamed thight head W hoop steel drum, with	F3F-2616 Rev.B Ed.02
minor corrugations	



DIMENSIONS:

Volume, I	H*Ø, mm	Head / Body / Bottom, mm
216.5	885*585	1.0 / 0.8 / 1.0
216.5	885*585	0.9 / 0.8 / 0.9

MAXIMUM DEGREE OF FILLING IN LITER AT 15 °C, SHALL BE:

Initial boiling	< 60	>= 60 < 100	>= 100 < 200	>= 200 < 300	>= 300
point in °C					
Degree of filling	195.7	200.1	204.4	208.8	213.1
in liter					

NET0335B Page 1 of 3

NET AS Blekebakkvegen 45 N-3950 Brevik Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E



CLOSING MECHANISM:

#: Bungs	Producer	Drawings	Material	Gasket	Torque
1: 2"	Tri-Sure	TSN-925089	Steel	PE / EPDM /	20 Nm
				Nitril	
2: 2" Ventilated	Tri-Sure	TSN-939323	Steel	PE / EPDM /	20 Nm
				Nitril	
3: 3/4"	Tri-Sure	TSN-925096	Steel	PE / EPDM /	15 Nm
				Nitril	



LEGISLATION:

The approval is valid for a maximum of five years, provided that no changes are made to the packaging design, materials, dimensions, closure system, or method of construction. This certificate may be withdrawn at any time. For the current valid version, please refer to the official publication at www.net17025.com/Sertifisering/UN_ADR/cid/30758/.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 2023/4375 PRAX.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

6.1.5.3 Drop test

6.1.5.4 Leakproofness test

6.1.5.5 Internal hydraulic pressure test

6.1.5.6 Stacking test

APPROVAL IS VALID FOR:

The packaging shall always be used according to the requirement of the applicable UN-code and its packaging instruction.

Content	Max. vapour pressure, kPa at +50°C
Liquid substances that do not adversely affect the	200
packaging materials	

NET0335B Page 2 of 3

NET AS Blekebakkvegen 45 N-3950 Brevik Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E



DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET0335B	15.04.2011	NET	Type approval
NET0336B	15.04.2011	NET	Type approval
NET03T15	27.02.2012	NET	Type approval /
			Technical evaluation
NET0335E2	22.04.2025	NET	Additional type test

VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.

The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in NS-EN ISO 16106:2020.

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with NS-EN ISO/IEC 17025:2017 approved by Norsk Akkreditering and according to NS-EN ISO 16495:2022.

BREVIK, NORWAY

20.05.2025 CERTIFICATE IS VALID UNTIL:

Control Officer

30.04.2030

Mathias Werner Certification Officer

Nordisk Emballasje Testing Certification

his Weme

NET0335B Page 3 of 3

Telephone +47 900 17025 VAT No.: 990 793 840 Bank account: 6250.05.22351 E-mail: info@net17025.com Web: www.net17025.com GPS: 59°03'25" N 9°40'70" E