


TYPE APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET4008A


HOLDER OF CERTIFICATE:

VPK Packaging AB
MANUFACTURER:

VPK Packaging AB, Gamla Bruksgatan 70, SE-668 40
Bäckefors, Sweden

MARKING ON PACKAGING:

Each packaging intended for use under ADR must bear markings that are durable, legible, and placed in a location where they are easily visible. Letters, numerals, and symbols must be at least 12 mm in height. Each large packaging (LP) must also be marked with the maximum permitted stacking load, in accordance with ADR 6.6.3.3.1 (as shown in the figure to the right).

 **50GW/Y/MMYY/N/NET4008A - ID/0/70**

	: The United Nations symbol
50GW	: Fibreboard large packaging; for pallet-free transport using a dedicated roller conveyor system at plant and in vehicle
Y	: Packaging group II and III
MMYY	: To be replaced with the month and year (last two digits) of manufacture
N	: Norway, the state authorizing the allocation of the mark
NET4008A-ID	: Identification of the LP followed by "ID" to be replaced by the name or symbol of the manufacturer
0	: The stacking test load in kg
70	: The maximum permissible gross mass in kg

PRODUCT:

Description/ Method of manufacture	Drawing	Material	External dimensions: L*W*H, mm
FEFCO 0904 and 0911, slotted type, glued and stitched	S851328 & S851329 02/06/25	Corrugated fibreboard, double wall board, details in report	1031*821*806


DIMENSIONS:

Volume, l	Internal dimensions: L*W*H, mm	Thickness, mm
639	1017*793*792	6.9

CLOSING MECHANISM:

Closure type	Description
Slotted tray, used as lid and bottom	S851329 02/06/25, identical material as in sleeve, details in report
Two staples are placed in each corner to assemble the trays, Fefco 0911, with two additional staples in each corner to attach the trays to the sleeve, Fefco 0904, 16 staples in total	Josef Kihlberg, JK561-15, undefined Steel
Tape applied in four vertical strips on each short and long side. Positioned 100 mm from each corner and extends 200 mm over the edge of the top and bottom, providing a 100 mm overlap onto the side wall for each strip, 16 in total	Etab, 50 mm, strapping tape glass fibre reinforced PP-film

INNER PACKAGING:

Type	Description	Material	Dimensions
ETI-05019	Plastic drum	PP	5 L
ETI-96008	Plastic drum	PP	2 L
BVT31918	Plastic box	PP	30 L
BVT319116	Plastic box	PP	60 L
Yellow bag	Blown film	LLD PE	1100*365*0.09 mm



LEGISLATION:

The approval is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. This certificate is liable to withdrawal at any time, to ensure validation check the published version on the Internet (www.net17025.com/Sertifisering/UN_ADR/cid/30758/).

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 2023/4375 PRAX.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

6.6.5.3.1 Bottom lift test

6.6.5.3.4 Drop test

APPROVAL IS VALID FOR:

The packaging shall always be used according to the requirement of the applicable UN-code and its packaging instruction LP 621

Content

UN 3291 - CLINICAL WASTE, UNSPECIFIED, N.O.S. Use and transport require sufficient absorbent material for any free liquids. Sharp objects are only permitted in approved sharps containers. All inner packaging combinations are allowed, provided the maximum gross mass does not exceed 70 kg.

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET4008A	12.05.2025	NET	Type approval

VALIDITY:

The continued validity of the type approval requires that the holder of the certificate and/ or the manufacturer inform NET certification that has approved its type of packaging of any changes to the characteristics of the type or anything that can influence on the transport safety on the specific design so that it can be verified that the type of packaging continues to comply with packaging tested as base for the original type approval.


The validity of the type approval assume regular verification by means of periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance program which satisfies NET Certification, in order to ensure that each packaging meets the requirements in ADR and the guidelines in NS-EN ISO 16106:2020.

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with NS-EN ISO/IEC 17025:2017 approved by Norsk Akkreditering and according to NS-EN ISO 16495:2022.



BREVIK, NORWAY

05.06.2025 CERTIFICATE IS VALID UNTIL:**31.05.2030**

Mathias Werner
Certification Officer



Rune Madsen Fink
Control Officer

Nordisk Emballasje Testing Certification