

**TYPE APPROVAL OF PACKAGING FOR
TRANSPORTATION OF DANGEROUS GOODS
CERTIFICATE NO.: NET19001A**

HOLDER OF CERTIFICATE:

AB Karl Hedin

1704 kg max

MANUFACTURER:

AB Karl Hedin, Box 2008, 737 02 Fagersta, Sweden

MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 12 mm high. Each LP shall also be marked with maximum permitted stacking load according to ADR 6.6.3.3.1 (as shown in figure to right).



(u n) 50D/Y/MMYY/N/NET19001A-ID/3068/568

- (u n) : The United Nations symbol
- 50D : Large Packaging, plywood
- Y : Packaging group II and III
- MMYY : To be replaced with the month and year, last two digits, of manufacturer
- N : Norway, the state authorizing the allocation of the mark
- NET19001A - ID : Identification of the LP followed by "ID" to be replaced by the name or symbol of the manufacturer
- 3068 : The stacking test load in kg
- 568 : The maximum permissible gross mass in kg

PRODUCT:

Description/ Method of manufacture	Drawings	Material
Screw-constructed plywood crate large packaging	Cube V6 Rev.1 03.04.24	5 layers of plywood, Pine



DIMENSIONS:

Volume, l	Internal dimensions: L*W*H, mm	External dimensions: L*W*H, mm	Thickness, mm
434	834*790*675	862*800*838	9

CLOSING MECHANISM:

Lid with alternative plastic straps	Producer	Drawings/ Description	Material
Lid	Karl Hedin	Cube V6 Rev.1 03.04.24	5 layers of plywood, Pine
Plastic straps, 3 pc	Fromm Packaging Systems	19 * 1 mm	PET
Plastic straps, 4 pc	Fromm Packaging Systems	16 * 1 mm	PET



LEGISLATION:

NET issues this certification pursuant to delegated authority from the Norwegian Directorate for Civil Protection (DSB), in accordance with the Regulation of 1 April 2009 No. 384 on the land transport of dangerous goods, Chapter 6a (ref. 2023/4375 PRAX). NET is designated as the competent body for allocation of the UN mark on packagings, including IBCs and large packagings, as published by the United Nations (UNECE) list of competent authorities.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

6.6.5.3.1 Bottom lift test

6.6.5.3.3 Stacking test

6.6.5.3.4 Drop test

APPROVAL IS VALID FOR:

The packaging shall always be used according to the requirement of the applicable UN-code and its packaging instruction.

Prior to reuse, all UN-approved packagings intended for the transport of dangerous goods shall be inspected to confirm that they remain free from damage, corrosion, and contamination. Compliance with the original ADR type approval, including all applicable prototype test performance criteria, must be ensured.

Packagings showing any sign of reduced mechanical integrity shall be subject to reconditioning, repair,

or permanent withdrawal from service. All functional components - including closures, gaskets, and valves - must remain intact and fully operational to ensure continued conformity. Packagings that no longer fulfil these requirements shall not be reused for the transport of dangerous goods, in accordance with ADR 4.1.1.9.

Content	Dimensions, mm	Weight of content, kg
UN 3480, Lithium-ion battery	744*686*679	529

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET19001A	24.02.2024	NET	Type approval
NET190TE01	08.04.2024	NET	Technical evaluation
NET190TE02	31.05.2024	NET	Technical evaluation

VALIDITY:

This approval is valid for five (5) years, provided no modifications are made to the packaging design, materials, dimensions, closure system, or method of construction. The certificate may be withdrawn at any time. The published version on www.net17025.com/Sertifisering/UN_ADR/cid/30758/ shall always be considered the valid one. The certificate holder/manufacturer must notify NET Certification of any changes that may influence transport safety. Continued validity requires periodic audits by NET in accordance with NET Doc 2: "Production control agreement". The packaging shall be manufactured, reconditioned and tested under a quality assurance programme meeting ADR requirements and guidelines in NS-EN ISO 16106:2020.

TEST STANDARD:


All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with NS-EN ISO/IEC 17025:2017 approved by Norsk Akkreditering and according to NS-EN ISO 16495:2022 and NS-EN ISO 13274:2013.



BREVIK, NORWAY

05.06.2024 CERTIFICATE IS VALID UNTIL:

30.04.2029



Mathias Werner
Certification Officer



Rune Madsen Fink
Control Officer

Nordisk Emballasje Testing Certification