

**TYPE APPROVAL OF PACKAGING FOR
TRANSPORTATION OF DANGEROUS GOODS
CERTIFICATE NO.: NET0356F**

HOLDER OF CERTIFICATE:

Greif Sweden AB

MANUFACTURER:

Greif Sweden AB, Box 23, SE-311 23 Falkenberg, Sweden

MARKING ON PACKAGING:

Each packaging intended for use according to the ADR shall bear markings which are durable, legible and placed in a location as to be readily visible. Letters, numerals and symbols shall be at least 12 mm high. The packaging shall also be appropriately marked with the month of the manufacture. The period of use permitted for the carriage of dangerous substances shall be five years from the date of manufacture of the jerricans, except where a shorter period of use is prescribed because of the nature of the substance to be carried.

Ⓢ **3H1/X1.9/250/YR/N/NET0356F - ID**

Ⓢ : The United Nations symbol
 3H1 : Plastics jerricans, non-removable head
 X1.9 : Packaging group I, II and III, and relative density of the substance
 250 : Hydraulic test pressure in kPa
 YR : To be replaced with the last two digits of the year of manufacture
 N : Norway, the state authorizing the allocation of the mark
 NET0356F : Identification of the jerrican

PRODUCT:

Method of manufacture/ Description
Blow moulded stackable jerrican with min. wall thickness 1.68 mm, performed in HDPE, details in report.



DIMENSIONS:

# Jerrican weight, g	Volume, l	L*W*H, mm	Neck size, mm	Drawing
1: 885 - 1189	15.0	292*247*310	60	FB-0028 Rev A
2: 1033 - 1388	20.0	292*247*386	60	FB-0005 Rev B
3: 1189 - 1598	25.0	292*247*466	60	FB-0006 Rev B
4: 1247 - 1676	27.5	292*247*496	60	FB-0007 Rev B

CLOSING MECHANISM:

#: Screw cap	Producer	Drawings	Material	Gasket	Torque
1: 60 mm	Tri-Sure	TSF - 504224-2	HDPE	Washer, PE foam	25 Nm
2: 60 mm	Tri-Sure	F4P - 2015	HDPE	Washer, PE foam	25 Nm
3: 60 mm	Tri-Sure	TSF - 505112	HDPE	Washer, PE foam	25 Nm
4: D17, Vented 60 mm	Tri-Sure	TSF - 504351	HDPE	Washer, PE foam	25 Nm
5: 60 mm	Tri-Sure	TSF - 505512	Borealis BS2581	Washer, PE foam	25 Nm
6: 60 mm	Tri-Sure	TSF - 505972	HDPE	Washer, PE foam	25 Nm
7: 60 mm	Bergi Plast	00 - 1836	HDPE	EPE 300	25 Nm
8: 60 mm	Kunststofftechnik	V-6170 SK 61-6 R	HDPE	Washer, PE foam	25 Nm
9: 60 mm	Procap	09 s 41 LB 13-01P /10013577	HDPE	Induction liner	25 Nm
11: 60 mm	Procap	BV0600C B	HDPE	ALU 30my/PET12my /PE60my	25 Nm
12: 60 mm carbon black free	Tri-Sure	TSF-506492	HDPE	Washer, PE foam	25 Nm





LEGISLATION:

NET issues this certification pursuant to delegated authority from the Norwegian Directorate for Civil Protection (DSB), in accordance with the Regulation of 1 April 2009 No. 384 on the land transport of dangerous goods, Chapter 6a (ref. 2023/4375 PRAX). NET is designated as the competent body for allocation of the UN mark on packagings, including IBCs and large packagings, as published by the United Nations (UNECE) list of competent authorities.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

6.1.5.2.6 Chemical compatibility

6.1.5.3 Drop test

6.1.5.4 Leakproofness test

6.1.5.5 Internal pressure test

6.1.5.6 Stacking test

6.1.5.7 Supplementary permeability test

APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances covered by the liquids listed in the table below. The liquids marked with letter A - F are referring to standard liquids listed in ADR 6.1.6.1 and verified by chemical compatibility testing, ADR 6.1.5.2.6, to this specific liquid.

The dangerous substances allowed to transport in the packaging after chemical compatibility with these liquids, are listed in the "Assimilation list" table 4.1.1.21.6 in ADR. Transport of the substance is only allowed if the approval of the standard liquid(S), covered by "Rule for collective entries", has the same or higher relative density as the substance to be transported.

The packaging shall always be used according to the requirements of the applicable UN-code and its packaging instructions.

Prior to reuse, all UN-approved packagings intended for the transport of dangerous goods shall be inspected to confirm that they remain free from damage, corrosion, and contamination. Compliance with the original ADR type approval, including all applicable prototype test performance criteria, must be ensured.

Packagings showing any sign of reduced mechanical integrity shall be subject to reconditioning, repair, or permanent withdrawal from service. All functional components - including closures, gaskets, and valves - must remain intact and fully operational to ensure continued conformity.

Packagings that no longer fulfil these requirements shall not be reused for the transport of dangerous goods, in accordance with ADR 4.1.1.9.

Content	Max. relative density	Max. vapour pressure, kPa at +50°C
Standard liquid D: Mixture of hydrocarbons	1.0	200
Standard liquid C: n-Butyl acetate	1.0	200
Standard liquid B: Acetic Acid	1.2	200
Standard liquid A: Wetting Solution	1.2	200
Standard liquid F: Water	1.9	200
Standard liquid E: Nitric Acid	1.4	200

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET0356F	25.09.2025	NET	Type test
NET0356F2	06.01.2026	NET	Type test
NET0356F3	06.01.2026	NET	Type approval
NET03TE47	04.03.2026	NET	Technical evaluation

VALIDITY:

This approval is valid for five (5) years, provided no modifications are made to the packaging design, materials, dimensions, closure system, or method of construction.

The certificate may be withdrawn at any time.

The published version on www.net17025.com/Sertifisering/UN_ADR/cid/30758/ shall always be considered the valid one.

The certificate holder/manufacturer must notify NET Certification of any changes that may influence transport safety.

Continued validity requires periodic audits by NET in accordance with NET Doc 2: "Production control agreement".

The packaging shall be manufactured, reconditioned and tested under a quality assurance programme meeting ADR requirements and guidelines in NS-EN ISO 16106:2020.

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with NS-EN ISO/IEC 17025:2017 approved by Norsk Akkreditering and according to NS-EN ISO 16495:2022 and NS-EN ISO 13274:2013.



BREVIK, NORWAY

05.03.2026 CERTIFICATE IS VALID UNTIL:

28.02.2031


 Mathias Werner
 Certification Officer



 Rune Madsen Fink
 Control Officer

Nordisk Emballasje Testing Certification