

TYPE APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET7908A

HOLDER OF CERTIFICATE:
Dolav Plastic Products Ltd.

890 kg max

MANUFACTURER: Dolav Plastic Products Ltd., Kibbutz Dvir 8533000, Israel

MARKING ON PACKAGING:

All packagings intended for use under ADR shall bear markings that are durable, clearly legible, and positioned in a location where they are readily visible. The minimum height for letters, numerals, and symbols is 12 mm. In addition, each IBC shall be marked with the maximum permitted stacking load, in accordance with ADR 6.5.2.2.1 (refer to the figure on the right).



11H2/X/MMYY/N/NET7908A - ID/1602/445

	: The United Nations symbol
11H2	: Rigid plastics IBCs, freestanding, for solids
X	: Packaging group I
MMYY	: To be replaced with the month and year (last two digits) of manufacturer
N	: Norway, the state authorizing the allocation of the mark
NET9708A - ID	: Identification of the IBC followed by "ID" to be replaced by the name or symbol of the manufacturer
1602	: Stacking test load in kg
445	: Maximum gross mass in kg

PRODUCT:

Description/ Method of manufacture	Drawing
Rectangular rigid plastic containers injection moulded in HDPE structural foam.	2400300002217



DIMENSIONS:

Volume, l	External dimensions: L*W*H, mm	Internal dimensions: L*W*H, mm
610	1200*1000*762	1120*928*605

CLOSING MECHANISM:

Closure type
Lid secured by two polyester straps with ratchet tensioners in accordance with EN 12195-2. For transport, both straps shall be fitted and fully tensioned.

LEGISLATION:

NET issues this certification pursuant to delegated authority from the Norwegian Directorate for Civil Protection (DSB), in accordance with the Regulation of 1 April 2009 No. 384 on the land transport of dangerous goods, Chapter 6a (ref. 2023/4375 PRAX). NET is designated as the competent body for allocation of the UN mark on packagings, including IBCs and large packagings, as published by the United Nations (UNECE) list of competent authorities.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATORY BASIS FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests have been performed and approved in accordance with the above regulations.

6.5.6.4 Bottom lift test

6.5.6.6 Stacking test

6.5.6.9 Drop test

APPROVAL IS VALID FOR:

The IBC shall always be used in accordance with the requirements of the applicable UN code and corresponding packaging instruction. The contents must not adversely affect the packaging materials.

Prior to reuse, all UN-approved packagings intended for the transport of dangerous goods shall be inspected to confirm that they remain free from damage, corrosion, and contamination. Compliance with the original ADR type approval, including all applicable prototype test performance criteria, must be ensured.

Packagings showing any sign of reduced mechanical integrity shall be subject to reconditioning, repair, or permanent withdrawal from service. All functional components - including closures, gaskets, and valves - must remain intact and fully operational to ensure continued conformity.

Packagings that no longer fulfil these requirements shall not be reused for the transport of dangerous goods, in accordance with ADR 4.1.1.9.

Approved content

Solids that do not adversely affect the packaging materials

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
7613211167/2	31.05.2026	The Standards Institution of Israel, Mechanics & Hydraulics Laboratory	Type approval

VALIDITY:

This approval is valid for five (5) years, provided no modifications are made to the packaging design, materials, dimensions, closure system, or method of construction.

The certificate may be withdrawn at any time.

The published version on www.net17025.com/Sertifisering/UN_ADR/cid/30758/ shall always be considered the valid one.

The certificate holder/manufacture must notify NET Certification of any changes that may influence transport safety.

Continued validity requires periodic audits by NET in accordance with NET Doc 2: "Production control agreement".

The packaging shall be manufactured, reconditioned and tested under a quality assurance programme meeting ADR requirements and guidelines in NS-EN ISO 16106:2020.

BREVIK, NORWAY

11.08.2026

CERTIFICATE IS VALID UNTIL:

31.08.2031


Anita Gusfre Thoner
Certification Officer



Rune Madsen Fink
Control Officer

Nordisk Emballasje Testing Certification