

TYPE APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET7906A

HOLDER OF CERTIFICATE:
Dolav Plastic Products Ltd.

1242 kg max

MANUFACTURER: Dolav Plastic Products Ltd., Kibbutz Dvir 8533000, Israel

MARKING ON PACKAGING:

Each packaging intended for use under ADR must bear markings that are durable, legible, and placed in a location where they are easily visible. Letters, numerals, and symbols must be at least 12 mm in height. Each large packaging (LP) must also be marked with the maximum permitted stacking load, in accordance with ADR 6.6.3.3.1 (as shown in the figure to the right).



50H/Y/MMYY/N/NET7906A - ID/2236/621

	: The United Nations symbol
50H	: Plastics large packaging
Y	: Packaging group II and III
MMYY	: To be replaced with the month and year (last two digits) of manufacture
N	: Norway, the state authorizing the allocation of the mark
NET7906A - ID	: Identification of the LP followed by "ID" to be replaced by the name or symbol of the manufacturer
2236	: The stacking test load in kg
621	: The maximum permissible gross mass in kg

PRODUCT:

Description/ Method of manufacture	Drawing
Rectangular rigid plastic container injection moulded in HDPE structural foam.	2403700002 version B



DIMENSIONS:

Volume, l	External dimensions: L*W*H, mm	Internal dimensions: L*W*H, mm
1008	1600*1200*740	1529*1127*585

CLOSING MECHANISM:

Closure type
Lid secured by 10 metal latches, type AL-KO BV 20-3. For transport, all 10 latches shall be fully engaged.

LEGISLATION:

NET issues this certification pursuant to delegated authority from the Norwegian Directorate for Civil Protection (DSB), in accordance with the Regulation of 1 April 2009 No. 384 on the land transport of dangerous goods, Chapter 6a (ref. 2023/4375 PRAX). NET is designated as the competent body for allocation of the UN mark on packagings, including IBCs and large packagings, as published by the United Nations (UNECE) list of competent authorities.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATORY BASIS FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

TESTS CARRIED OUT:

Prototype tests performed and approved according to the above regulations:

6.6.5.3.1 Bottom lift test

6.6.5.3.3 Stacking test

6.6.5.3.4 Drop test

APPROVAL IS VALID FOR:

The packaging shall always be used according to the requirement of the applicable UN-code and its packaging instruction.

Prior to reuse, all UN-approved packagings intended for the transport of dangerous goods shall be inspected to confirm that they remain free from damage, corrosion, and contamination. Compliance with the original ADR type approval, including all applicable prototype test performance criteria, must be ensured.

Packagings showing any sign of reduced mechanical integrity shall be subject to reconditioning, repair, or permanent withdrawal from service. All functional components - including closures, gaskets, and valves - must remain intact and fully operational to ensure continued conformity.

Packagings that no longer fulfil these requirements shall not be reused for the transport of dangerous goods, in accordance with ADR 4.1.1.9.

Approved content

Solid dangerous goods of packaging group II and III, in inner packagings or as articles, that do not adversely affect the packaging materials, where permitted by the applicable packing instruction for large packaging type 50H.

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
7613211164	26.05.2026	11H2/X/MMYY/N/NET790 8A - ID/1602/445	Type approval

VALIDITY:

This approval is valid for five (5) years, provided no modifications are made to the packaging design, materials, dimensions, closure system, or method of construction.

The certificate may be withdrawn at any time.

The published version on www.net17025.com/Sertifisering/UN_ADR/cid/30758/ shall always be considered the valid one.

The certificate holder/manufacturer must notify NET Certification of any changes that may influence transport safety.

Continued validity requires periodic audits by NET in accordance with NET Doc 2: "Production control agreement".

The packaging shall be manufactured, reconditioned and tested under a quality assurance programme meeting ADR requirements and guidelines in NS-EN ISO 16106:2020.

BREVIK, NORWAY

11.08.2026

CERTIFICATE IS VALID UNTIL:

31.08.2031


Anita Gusfre Thoner
Certification Officer



Rune Madsen Fink
Control Officer

Nordisk Emballasje Testing Certification