



**PRODUCT APPROVAL OF PACKAGING  
FOR TRANSPORTATION OF DANGEROUS GOODS  
CERTIFICATE NO.: NET9503B**

HOLDER OF CERTIFICATE:  
**Norsk Formblåsing AS**

**MANUFACTURER:** Norsk Formblåsing AS, Merdeveien 12 B, 3676 Notodden, Norway

**MARKING ON PACKAGING:**  **3H1/X/250/YR/N/NET9503B - ID**

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

The packaging shall also be appropriately marked with the month of the manufacture.

**PRODUCT:**

Packaging code	Description	Drawings	Material
3H1	Plastics jerricans, non-removable head	20.06.2006	Finathene 49080 UV

**CLOSING MECHANISM:**

# : Closure type	Producer	Drawings	Material	Gasket	Torque
Screw cap	Norsk Formblåsing	20062006	Borealis MG7541S	Nitrile Rubber NBR Super	3 Nm



**DIMENSIONS:**

Packaging weight, g	Volume, l	Height, mm	Width, mm	Length, mm	Neck size, mm
1340-1407	20.0	445	203	335	40

**APPROVAL:**

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

**REGULATIONS BASED UPON FOR APPROVAL:**

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.  
 RID, International Regulations on Transport of Dangerous Goods by Rail.  
 UN Recommendations on the Transport of Dangerous Goods.  
 IMDG, International Maritime Dangerous Goods Code, for sea transport.  
 ICAO Technical Instructions for the Safe Transport of Dangerous Goods by Air.  
 IATA Dangerous Goods Regulations, for the air transport.

**APPROVAL IS VALID FOR:**

The packaging is valid for packaging group I, II and III containing liquid substances that do not adversely affect the packaging materials. Permeability test has been carried out according to ADR 6.1.5.7. Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	Max. relative density	Max. vapour pressure, kPa at +50°C
Acetic acid	1.1	200
White spirit	1.0	200

**DOCUMENTS BASED UPON FOR APPROVAL:**

Report id.	Date	Issued by	Scope
P603035C	16.10.2006	SP	Type approval
NET1503A	12.08.2008	NET	Type approval

LERUM, SWEDEN

**28.01.2015** CERTIFICATE IS VALID UNTIL:

**31.01.2020**



Susanne E. Dalhberg  
 Certification Officer



Rune Madsen Fink  
 Control Officer

*Nordisk Emballasje Testing AS Certification*