



PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NETO209C

HOLDER OF CERTIFICATE:

RPC Promens AS, Kambo Packaging

MANUFACTURER: RPC Promens AS, Kambo Packaging, Boks 3054, N-1506 Moss,

Norway

MARKING ON PACKAGING: (3) 3H1/Y1.9/150/YR/N/NET0209C - ID

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

The packaging shall also be appropriately marked with the month of the manufacture.

PRODUCT:

Packaging code	Description	Drawing	Material
3H1	Plastics jerricans,	B-30799 (9436)	Sabic B5210
	non-removable head		

CLOSING MECHANISM:

Closure type	Producer	Drawings	Material	Gasket	Torque
Screw cap	Modulpac AB	40BO	Outer cap:	PE foam	5 Nm
			HMA025 - Inner		
			cap: HYA600		
Screw cap	Modulpac AB	40PM-UN	ExxonMobil:	Cone sealing	5 Nm
			HYA600		
Screw cap	RPC Promens	S-3101	ExxonMobil:	Cone sealing	6 Nm
	AS, Kambo	16.06.15	HYA600		







NET0209C Page 1 of 3

Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E





DIMENSIONS:

Packaging	Volume, I	Height, mm	Width, mm	Length, mm	Neck size, mm
weight, g					
258 - 271	5	305	130	200	40

APPROVAL:

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III, with max vapour pressure 142 kPa at 50°C, containing liquid substances that do not adversely affect the packaging materials. Permeability test has been carried out according to ADR 6.1.5.7. Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	Max. relative density
Water	1.9
n-Butyl acetate	1.0
White spirit	1.0
Wetting solution	1.2
Acetic acid	1.2

DOCUMENTS BASED UPON FOR APPROVAL:

DOCCITETIO DIOLE CI CITTORIA IL ROVILLE				
Report id.	Date	Issued by	Scope	
333501	06.06.2000	BVT	Type approval	
NET0209C	14.01.2009	NET	Type testing	
NET02T03	06.08.2010	NET	Type testing	
NET02T07	07.06.2012	NET	Type testing	

Telephone +47 900 17025

E-mail: <u>info@net17025.com</u>

Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E





LERUM, SWEDEN

20.01.2016 CERTIFICATE IS VALID UNTIL:

31.01.2021

Susanne E. Dahlberg Certification Officer Rune Madsen Fink Control Officer

Nordisk Emballasje Testing AS Certification

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>

VAT No.: 990 793 840 Bank account: 6250.05.22351 GPS: 59°03'25" N 9°40'70" E