



PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET9304A

HOLDER OF CERTIFICATE: Haywood Roto Moulding Limited

MANUFACTURER:

Haywood Roto Moulding Limited, Brook House, 221 Bowling Back Lane, Bradford BD4 8SJ, UK Haywood Roto Moulding Limited, Green Grove Mill Dye House Lane, Rochdale OL16 2QN, UK

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

PRODUCT:

Packaging code	Description	Drawings	Material	
6HH1, Plastics receptacle	Rotationally moulded	45L Warboy	LMDPE	
with outer plastics drum				

CLOSING MECHANISM:

Closure type	Producer	Dimension, mm	Material	Gasket	Torque, Nm
Plain screw cap	Francis Ward	65	LMDPE	PE Foam	25
Vented screw	Francis Ward	65	LMDPE	PE Foam	25
сар					



DIMENSIONS:

Packaging	Tare mass, kg	Volume, I	Height, mm	Diameter, mm	Neck size, mm
weight (inner +					
outer), kg					
2.6 + 3.25	6.4	45	610	392	50

	NET9304A	Page 1 of 2	
Nordisk Emballasje Testing AS	Telephone	+47 900 17025	VAT No.: 990 793 840
Blekebakkvegen 45	E-mail:	info@net17025.com	Bank account: 6250.05.22351
N-3950 Brevik	Web:	www.net17025.com	GPS: 59°03'25" N 9°40'70" E



APPROVAL:

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances that do not adversely affect the packaging materials. Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	-	Max. vapour pressure, kPa at +50°C
Water	1.9	114

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
11D19-0621	01.02.2012	Pira International	Type approval
NET9300	30.04.2015	NET	Type approval

LERUM, SWEDEN

11.05.2016 CERTIFICATE IS VALID UNTIL:

31.05.2021

medallim

Susanne E. Dahlberg Certification Officer

Nordisk Emballasje Testing AS Certification

Rune Madsen Fink Control Officer