



**PRODUCT APPROVAL OF PACKAGING
FOR TRANSPORTATION OF DANGEROUS GOODS
CERTIFICATE NO.: NET0213C**

HOLDER OF CERTIFICATE:
RPC Promens AS, Kambo

MANUFACTURER: RPC Promens AS, Kambo, Boks 3054, N-1506 Moss, Norway

MARKING ON PACKAGING:  **3H1/Y/100/YR/N/NET0213C - ID**

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

The packaging shall also be appropriately marked with the month of the manufacture.

PRODUCT:

Packaging code	Description	Drawings	Material
3H1, 5 L	Plastics jerricans, non-removable head	B-30926	HDPE, Sabic B5210
3H1, 3 L	Plastics jerricans, non-removable head	B30953	HDPE, Sabic B5210

CLOSING MECHANISM:

Closure type	Producer	Drawings	Material	Gasket	Torque, Nm
Screw cap childproof	Modulpac AB	40BGPP	Exxon Mobil HDPE HYA 600	AlkoZell	7



DIMENSIONS:

Packaging weight, g	Volume, l	Length, mm	Width, mm	Height, mm	Neck size, mm
241-253	5.0	193	134	320	40
190-200	3.0	193	134	228	40

APPROVAL:

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.
 ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.
 RID, International Regulations on Transport of Dangerous Goods by Rail.
 IMDG, International Maritime Dangerous Goods Code, for sea transport.
 ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.
 IATA, Dangerous Goods Regulations, for the air transport.

APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid substances that do not adversely affect the packaging materials. Permeability test has been carried out according to ADR 6.1.5.7. Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	Max. relative density	Max. vapour pressure, kPa at +50°C
Water	1.2	114
White spirit	1.0	114

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
1303635	31.02.2006	DTI	Type testing
NET2801A	20.10.2008	NET	Additional type testing
NET0213C	08.01.2009	NET	Type testing
NET0213C-1	13.12.2010	NET	Additional type testing
NET02TE01	13.07.2011	NET	Technical Evaluation
NET0217C-1	01.11.2011	NET	Additional type testing

LERUM, SWEDEN

03.03.2017 CERTIFICATE IS VALID UNTIL:

31.03.2022


 Susanne E. Dahlberg
 Certification Officer



 Rune Madsen Fink
 Control Officer

Nordisk Emballasje Testing AS Certification