



# PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NET6720A

# HOLDER OF CERTIFICATE: Emballator Ulricehamns Bleck AB

## MANUFACTURER:

Emballator Ulricehamns Bleck AB, Maskinvägen 10, SE-52321 Ulricehamn, Sweden

### MARKING ON PACKAGING:

1A2/Y2.0 Z3.0/100/YR/N/NET6720A - ID

"YR" to be replaced with the two last digits of the year. "ID" to be replaced by any identification as decided by the manufacturer.

### **PRODUCT:**

Packaging code	Description	Material
1A2, Steel drums, removable	UN can serie 105, 0.33   - 1.5	TH415(T61)
head		

### **CLOSING MECHANISM:**

Closure type	Producer	Drawings	Material
Lid	Emballator Ulricehamns	6183-06	TS275(T57)
	Bleck		
Lid with opening for	Emballator Ulricehamns	6189-03	TS275(T57)
spout, P2	Bleck		
Lid with opening for	Emballator Ulricehamns	6191-01	TS275(T57)
spout	Bleck		
Pull up spout with cap	Rieke Germany GmbH	3-3.290A4	EVA/LDPE / HDPE





# **DIMENSIONS:**

Volume, l	Height, mm	Diameter, mm	Head / Body /	Drawing
			Bottom, mm	
0.33 - 1.5	55 - 198	106	0.20 / 0.20 / 0.18	EPR-105-1001-01 /
				EPR-105-1001-01
				(150615)

# **APPROVAL:**

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

# **REGULATIONS BASED UPON FOR APPROVAL:**

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

### **APPROVAL IS VALID FOR:**

The packaging is valid for packaging group II and III containing liquid substances that do not adversely affect the packaging materials.

Content	Max. relative density		Max. vapour pressure, kPa at +50°C
Liquid	2.0	II	114
Liquid	3.0	III	114

### DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
P605207	03.07.2007	SP	Type apporoval
NET6720A	18.06.2015	NET	Selective type approval
NET6720A2	30.03.2017	NET	Additional test, increased
			density



INTERNATIONAL CERTIFICATE

PORSGRUNN, NORWAY

**06.04.2017** CERTIFICATE IS VALID UNTIL:

30.04.2022

laci A. Joha

Geir Morten Johansen Certification Officer

Nordisk Emballasje Testing AS Certification

Rune Madsen Fink Control Officer