



**PRODUCT APPROVAL OF PACKAGING
FOR TRANSPORTATION OF DANGEROUS GOODS
CERTIFICATE NO.: NET0401A**

HOLDER OF CERTIFICATE:
RPC Packaging AS, avd. Kambo

MANUFACTURER: RPC Packaging AS, avd. Kambo, Boks 3054, N-1506 Moss, Norway

MARKING ON PACKAGING:  **3H1/Y1.0/100/YR/N/NET0401A - ID**

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

The packaging shall also be appropriately marked with the month of the manufacture.

PRODUCT:

Packaging code	Description	Drawings	Material
3H1, 15 L	Plastics jerricans, non-removable head	A0-015-E	HDPE, Total 51090

CLOSING MECHANISM:

Closure type	Producer	Drawings	Material	Gasket	Torque
Screw cap	Promens AS, Kambo	A3-030-E	HDPE, Sabic B5823	Polycell 300	15 Nm



DIMENSIONS:

Packaging weight, g	Volume, l	Length, mm	Width, mm	Height, mm	Neck size, mm
900 - 964	15.0	292	196	401	55

APPROVAL:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

REGULATIONS BASED UPON FOR APPROVAL:

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

UN Recommendations on the Transport of Dangerous Goods.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA Dangerous Goods Regulations, for the air transport.

APPROVAL IS VALID FOR:

The packaging is valid for packaging group II and III containing liquid according to the compatibility testing carried out according to ADR/RID with the content listed below:

Content	Max. relative density	Max. vapour pressure, kPa at +50°C
Synteko Classic 1646 (UN1263)	1.0	114

DOCUMENTS BASED UPON FOR APPROVAL:

Report id.	Date	Issued by	Scope
NET0401A	14.04.2008	NET	Type approval

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001.

The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.



PORSGRUNN, NORWAY

30.04.2018 CERTIFICATE IS VALID UNTIL:

30.04.2023

A handwritten signature in blue ink, reading 'Geir M. Johansen'.

Geir Morten Johansen
Certification Officer

A handwritten signature in blue ink, reading 'Rune Madsen Fink'.

Rune Madsen Fink
Control Officer

Nordisk Emballasje Testing AS Certification

A large, faint watermark logo in the background, consisting of a stylized white cross or plus sign centered within a light blue circular shape.