



# PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NETO 130A

# **HOLDER OF CERTIFICATE:**

# **Emballator Mellerud Plast AB**

MANUFACTURER: Emballator Mellerud Plast AB, Box 83, SE-464 22 Mellerud,

**SWEDEN** 

MARKING ON PACKAGING: (3) 3H1/Y1.9/150/YR/N/NET0130A - ID

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

The packaging shall also be appropriately marked with the month of the manufacture.

## **PRODUCT:**

Packaging code	Description	Drawings	Material
3H1, plastics jerricans	Non-removable head	PR-1308 151008	HDPE, details in report



#### **CLOSING MECHANISM:**

CEOSING FIECHANISM					
#: Screw cap,	Producer	Drawings	Material	Gasket	Torque
40 mm					
1:Child resistant	Emballator	40-948/901G	HDPE, details in	Cone	5 Nm
std tread	Växjöplast AB		report		
2:Child resistant	Emballator	40-983/901G	HDPE, details in	EPE/PET	5 Nm
std tread	Växjöplast AB		report		
3:Child resistant	Emballator	40-985/901G	HDPE, details in	EPE/PET	5 Nm
std tread	Växjöplast AB		report		
4:Child resistant	Emballator	40-900/901G	HDPE, details in	Cone	5 Nm
std tread	Växjöplast AB		report		
5:Child resistant	Emballator	40-255/901G	HDPE, details in	EPE/ALU	6 Nm
UN tread	Växjöplast AB		report		

NET0130A Page 1 of 4

Telephone +47 900 17025 E-mail: <u>info@net17025.com</u> Web: <u>www.net17025.com</u>





6:UN tread	Emballator	40-254GG	HDPE, details in	Cone	5 Nm
	Växjöplast AB		report		
7:Std tread	Emballator	40-900GG	HDPE, details in	Cone	5 Nm
	Växjöplast AB		report		
8:Std tread	Modulpac AB	40PMUN	HDPE, details in	Cone	5 Nm
			report		
9:Child resistant	Modulpac AB	40BO	HDPE, details in	Phan 200W	5 Nm
std tread			report		



 NET0130A
 Page 2 of 4

 Telephone
 +47 900 17025

 E-mail:
 info@net17025.com

 Web:
 www.net17025.com



#### **DIMENSIONS:**

#: Jerricans	Volume, I	Length, mm	Width, mm	Height, mm	Neck size, mm
weight, g					
1: 157 - 290	5.0	194	127	290	40 std tread
2: 230 - 290	5.0	194	127	290	40 UN tread
3: 138 - 255	4.0	194	127	250	40 std tread
4: 203 - 255	4.0	194	127	250	40 UN tread
5: 198 - 290	5.0	194	127	290	40 std tread
6: 176 - 255	4.0	194	127	250	40 std tread

#### APPROVAL:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

#### **REGULATIONS BASED UPON FOR APPROVAL:**

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

## **APPROVAL IS VALID FOR:**

The jerricans is valid for packaging group II and III containing liquid substances that do not adversely affect the packaging materials. Permeability test has been carried out, according to ADR 6.1.5.7, and approved for jerricans #2. Compatibility testing has been carried out according to ADR/RID with the content listed on next page:

Content	Max. relative density	Max. vapour pressure,	Max. vapour pressure,
		114 kPa at +50°C	143 kPa at +50°C
Water	1.9	Jerrican:1,3	Jerrican:2,4 Cap:5,6
		Cap:1-4,7,8,9	
Wetting solution	1.2	Jerrican:5,6	Jerrican:2,4 Cap:5,6
		Cap:1-4,7,8,9	
Acetic acid	1.1	Jerrican:1,3	Jerrican:2,4 Cap:5,6
		Cap:1-4,7,8,9	
n-Butylacetate	1.0	Jerrican:1,3	Jerrican:2,4 Cap:5,6
		Cap:1-4,7,8,9	
Mix. of hydrocarbons	1.0	Jerrican:1,3	Jerrican:2,4 Cap:5,6
		Cap:1-4,7,8,9	

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>





## **DOCUMENTS BASED UPON FOR APPROVAL:**

Report id.	Date	Issued by	Scope	
NET0130A	26.07.17	NET	Type approval	
NET0130A2	26.07.17	NET	Type testing; cap 2,3,4	
NET0130A5	14.09.17	NET	Type testing; J#2,	
			MixHC, n-Ba	
NET0130A6	15.04.19	NET	Type testing, caps 6-9,	
			n-Ba & Ws	

#### **TEST STANDARD:**

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.



PORSGRUNN, NORWAY

acir M. Johan

**09.05.2019** CERTIFICATE IS VALID UNTIL:

Control Officer

31.05.2024

Geir Morten Johansen Certification Officer

Nordisk Emballasje Testing AS Certification

NET0130A Page 4 of 4

NET Emballasje- og Produkttesting AS Blekebakkvegen 45 N-3950 Brevik Telephone +47 900 17025
E-mail: info@net17025.com
Web: www.net17025.com