



PRODUCT APPROVAL OF PACKAGING FOR TRANSPORTATION OF DANGEROUS GOODS CERTIFICATE NO.: NETO356D

HOLDER OF CERTIFICATE: **Greif Sweden AB**

MANUFACTURER: Greif Sweden AB, Box 23, SE-311 23 Falkenberg, Sweden

MARKING ON PACKAGING:

(1) 3H1/X1.9/250/YR/N/NET0356D - ID

"YR" to be replaced with the two last digits of the year.

"ID" to be replaced by any identification as decided by the manufacturer.

The packaging shall also be appropriately marked with the month of the manufacture.

PRODUCT:

Packaging code	Description	Drawings	Material
3H1 / 15 L	Plastics jerricans,	FB-0028 Rev A, FB-0029	HDPE
	non-removable head	Rev A	
3H1 / 20 L	Plastics jerricans,	FB-0025 Rev 01,	HDPE
	non-removable head	FB-0005, FB-0031 Rev	
		03	
3H1 / 25 L	Plastics jerricans,	FB-0026 Rev 01,	HDPE
	non-removable head	FB-0006 Rev 03	
3H1 / 27.5 L	Plastics jerricans,	FB-0027 Rev 01,	HDPE
	non-removable head	FB-0007 Rev 03	



Telephone +47 900 17025

E-mail: info@net17025.com

Web: www.net17025.com





CLOSING MECHANISM:

#: Screw cap	Producer	Drawings	Material	Gasket	Torque
•					
1: 60 mm	Tri-Sure	TSF - 504224-2	HDPE	Expended PE,	25 Nm
				O-ring	
2: 60 mm	Tri-Sure	F4P - 2015	HDPE	Washer, PEfoam	25 Nm
3: 60 mm	Tri-Sure	TSF - 505112	HDPE	Expended PE,	25 Nm
				O-ring	
4: D17, Vented	Tri-Sure	TSF - 504351	HDPE	Expended PE,	25 Nm
60 mm				O-ring	
5: 60 mm	Tri-Sure	TSF - 505512	Borealis BS2581	Expended PE,	25 Nm
				O-ring	
6: 60 mm	Tri-Sure	TSF - 505972	HDPE	Expended PE,	25 Nm
				O-ring	
7: 60 mm	Bergi Plast	00 - 1836	HDPE	EPE 300	25 Nm
8: 60 mm	Kunststofftechni	V-6170 SK 61-6	HDPE	PE	25 Nm
	k	R			
9: 60 mm	Procap	09 s 41 LB	HDPE	Induction liner	25 Nm
		13-01P			
		/10013577			
10: 25 mm	Modulpac	25PMPP	HDPE	PET/Alkozell/PE	3 Nm
				Т	
11: 60 mm	Procap	BV0600C B	HDPE	ALU	25 Nm
				30my/PET12my	
				/PE60my	
				,,	













 NET0356D
 Page 2 of 5

 Telephone
 +47 900 17025

 E-mail:
 info@net17025.com

 Web:
 www.net17025.com





DIMENSIONS:

D1112110101101					
# Packaging	Volume, I	Height, mm	Width, mm	Length, mm	Neck size, mm
weight, g					
1: 885 - 1189	15.0	310	247	292	60
2: 1033 - 1388	20.0	386	247	292	60
3: 1189 - 1598	25.0	466	247	292	60
4: 1247 - 1676	27.5	496	247	292	60

APPROVAL:

The certificate is valid for a maximum of five years, provided no modifications have been made to the packaging design, materials, dimensions, closure system or manner of construction. To ensure validation of the certificate, check the NET website.

NET issues the certification on described product according to delegated authority from Norwegian Directorate for Civil Protection and Emergency Planning (DSB): Legal regulations for Transportation of Dangerous Goods on road and railway - 06/6950-7/BJRU.

NET issues the certification on described product according to delegated authority from Norwegian Maritime Directorate (Sjøfartsdirektoratet) - 200705977-4/5367.1.

NET issues the certification on described product according to an agreement between Norwegian Civil Aviation Authority (Luftfartstilsynet) - 01.03.18 - 18/00114-8.

REGULATIONS BASED UPON FOR APPROVAL:

UN Recommendations on the Transport of Dangerous Goods.

ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID, International Regulations on Transport of Dangerous Goods by Rail.

IMDG, International Maritime Dangerous Goods Code, for sea transport.

ICAO, Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IATA, Dangerous Goods Regulations, for the air transport.

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>



APPROVAL IS VALID FOR:

The packaging is valid for packaging group I, II and III containing liquid substances that do not adversely affect the packaging materials. Permeability test has been carried out according to ADR 6.1.5.7. Compatibility testing has been carried out according to ADR/RID with the content listed below:

Content	Max. relative density	Max. vapour pressure, kPa at +50°C	Packaging #	Closure #
Mixture of	1.0	250	All items	All items
hydrocarbons				
n-Butyl acetate	1.0	250	All items	All items
Acetic acid	1.2	250	All items	All items
Wetting solution	1.2	250	All items	All items
Water	1.9	250	All items	All items

DOCUMENTS BASED UPON FOR APPROVAL:

	I	I	
Report id.	Date	Issued by	Scope
NET0356C	22.06.16	NET	Type approval
NET0356C2	08.08.16	NET	Additional test, ws
NET0356D	22.06.16	NET	Type approval
NET0356D2	08.08.16	NET	Additional test, ws, n-Ba
NET03TE28	02.09.16	NET	Calculation of production
			weights
NET0356D3	11.10.16	NET	Additional test, ws, wa
NET0356D4-K	24.11.16	NET	Additional test, cap 10 &
			13
NET0356D5	31.01.17	NET	Additional test, ws
			anti-glug

TEST STANDARD:

All tests are performed in accordance with NET accredited test method ATM001. The test method is accredited in accordance with ISO17025 approved by Norsk Akkreditering and based upon ISO16495 and ISO13274.



NET0356D Page 4 of 5

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>





BREVIK, NORWAY

31.05.2020 CERTIFICATE IS VALID UNTIL:

31.05.2025

Geir Morten Johansen Certification Officer

aci M. Johan

Rune Madsen Fink Control Officer

Nordisk Emballasje Testing AS Certification

Telephone +47 900 17025
E-mail: <u>info@net17025.com</u>
Web: <u>www.net17025.com</u>